



Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium, glass diffuser. 42° beam angle. Low recessed downlight with hole size Ø83mm

## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>903317  <b>Junistar Soft Black 740lm 2700K Ra 98 DALI-2 11W LED</b>            67 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903213  <b>Junistar Soft Black 740lm 2700K Ra 98 Trailing edge / Linect 11W LED</b>            67 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
 <p>903219  <b>Junistar Soft White 830lm 2700K Ra 98 DALI-2 11W LED</b>            75 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903211  <b>Junistar Soft White 830lm 2700K Ra 98 Trailing edge / Linect 11W LED</b>            75 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
 <p>903316  <b>Junistar Soft Black 760lm 3000K Ra 98 DALI-2 11W LED</b>            69 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903313  <b>Junistar Soft Black 760lm 3000K Ra 98 Trailing edge / Linect 11W LED</b>            69 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>903312  <b>Junistar Soft Brushed steel 790lm</b>  <b>3000K Ra 98 Trailing edge</b>  <b>11W LED</b>            72 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø94 x H53
 <p>903319  <b>Junistar Soft White 850lm 3000K Ra</b>  <b>98 DALI-2</b>  <b>11W LED</b>            77 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903311  <b>Junistar Soft White 850lm 3000K Ra</b>  <b>98 Trailing edge / Linect</b>  <b>11W LED</b>            77 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
 <p>903419  <b>Junistar Soft White 880lm 4000K Ra</b>  <b>98 DALI-2</b>  <b>11W LED</b>            80 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903411  <b>Junistar Soft White 880lm 4000K Ra</b>  <b>98 Trailing edge / Linect</b>  <b>11W LED</b>            80 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 42°, Direct, Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b>	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
<b>Accessories</b>				
 <p>9143  <b>Rehab Ring Black 133mm for Junistar, Uniled, Soft &amp; Jupiter</b></p>				Ø133 x H4
 <p>9236  <b>Rehab Ring Black 180mm for Junistar, Uniled, Soft &amp; Jupiter</b></p>				Ø180 x H45

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 9973 <b>Rehab Ring Brushed steel 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9233 <b>Rehab Ring Graphite 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9234 <b>Rehab Ring Graphite 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9327 <b>Rehab Ring Graphite 250mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø250 x H45
 9223 <b>Rehab Ring White 133mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø133 x H4
 9224 <b>Rehab Ring White 180mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø180 x H45
 9227 <b>Rehab Ring White 250mm for Junistar, Uniled, Soft &amp; Jupiter</b>				Ø250 x H45
 820489 <b>Sensor Dim Box White 200VA</b>				L220 x W75 x H34
 8246094429 <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b>				L270 x W75 x H35
 820090 <b>Emergencybox Adapter kit for downlight</b>				L250 x W13 x H13
 8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35