



Junistar IsoSafe TW is an attractive downlight for indoor use with 30° 360° stepless tilt. Our IsoSafe products can be mounted directly in insulation (IsoSafe).Junistar IsoSafe TW is equipped with the revolutionary Tunable White (TW) LEDDim technology. You can regulate both the lighting level and colour without extra cabling, using SG's TW LEDDim Smart dimmer. Control it manually or via the LEDDim app. When using the SG Smart Gateway, you can also set a daylight sequence which changes colour and intensity throughout the day. You can choose a standard rhythm or set your own. Junistar IsoSafe TW comes in two colour temperature ranges: 2700-6500K for traditional TW with the typical circadian spectrum, or 2000-4000K for typical residential use including warm and cosy colour temperatures. This is similar to DimToWarm, but with independent control of light level and colour temperature. Made of die-cast, powder-coated aluminium or brushed steel with glass diffuser. Tool-free mounting in mounting box for direct 230 V with loopable quick clips, automatic strain relief and Linec.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	912245 Junistar IsoSafe TW Black 460lm (@4000K) 2000-4000K Ra>90 TW LEDDim 8.5W LED 54 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP44/IP20	TW LEDDim	Recessed, Indoor Screwless terminal block	Ø94 x H54
	912243 Junistar IsoSafe TW White 500lm (@4000K) 2000-4000K Ra>90 TW LEDDim 8.5W LED 59 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP44/IP20	TW LEDDim	Recessed, Indoor Screwless terminal block	Ø94 x H54
	912244 Junistar IsoSafe TW Black 500lm (@6500K) 2700-6500K Ra>90 TW LEDDim 8.5W LED 59 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP44/IP20	TW LEDDim	Recessed, Indoor Screwless terminal block	Ø94 x H54
	912242 Junistar IsoSafe TW White 530lm (@6500K) 2700-6500K Ra>90 TW LEDDim 8.5W LED 62 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP44/IP20	TW LEDDim	Recessed, Indoor Screwless terminal block	Ø94 x H54
Accessories					
	9143 Rehab Ring Black 133mm for Junistar, United, Soft & Jupiter				Ø133 x H4
	9236 Rehab Ring Black 180mm for Junistar, United, Soft & Jupiter				Ø180 x H45
	9223 Rehab Ring White 133mm for Junistar, United, Soft & Jupiter				Ø133 x H4

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	9224			Ø180 x H45
	9227			Ø250 x H45