



Downlight for indoor use. Unique 45-degree tilt with minimal loss of light caused by it tilting towards the outer third of the luminaire dish. Replaceable dimmable LED GU10 bulb (included). Made of die-cast powder-coated aluminium or brushed steel. Ø83 hole dimensions.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 912170 Jupiter TEK White 350lm 2700K Ra>90 Trailing edge 6W LED 58 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,	Class II IP23	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H58
 912171 Jupiter TEK White 360lm 3000K Ra>90 Trailing edge 6W LED 60 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,	Class II IP23	Trailing edge	Recessed, Indoor Screwless terminal block	Ø94 x H58
Accessories				
 9973 Rehab Ring Brushed steel 133mm for Junistar, Uniled, Soft & Jupiter				Ø133 x H4
 9223 Rehab Ring White 133mm for Junistar, Uniled, Soft & Jupiter				Ø133 x H4
 9224 Rehab Ring White 180mm for Junistar, Uniled, Soft & Jupiter				Ø180 x H45
 9227 Rehab Ring White 250mm for Junistar, Uniled, Soft & Jupiter				Ø250 x H45