

LEDDim 400















Dimmer for mounting in wall box (EU) Setting of minimum level, 3–400 VA load, input for push dim functionality. Five-year system warranty for dimmer when it is used together with SG products.

LEDDim 400






Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 820411 LEDDim 2-pole White 400VA	IP20	Trailing edge	Recessed, Indoor	L84 x W84 x H42
Accessories				
 78501 Back box Black 1X	IP41		Surface, Indoor	L86 x W86 x H35
 78511 Back box Black 2X	IP41		Surface, Indoor	L86 x W157 x H35
 78521 Back box Black 3X	IP41		Surface, Indoor	L86 x W228 x H35
 820417 LEDDim 350/400/Smart Black SG Front				L83 x W83 x H29
 820579 LEDDim Black Adapter				
 820418 LEDDim 350/400/Smart Silver Elko Adapter				L55 x W55 x H12
 78500 Back box White 1X	IP41		Surface, Indoor	L86 x W86 x H35
 78510 Back box White 2X	IP41		Surface, Indoor	L86 x W157 x H35
 78520 Back box White 3X	IP41		Surface, Indoor	L86 x W228 x H35
 820330 LEDDim 350/400 White Adapter				L56 x W5 x H56
 820352 LEDDim 350/400/Smart White ABB Adapter				L55 x W55 x H10

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 820353 LEDDim 350/400/Smart White Schneider Adapter				L56 x W56 x H12
 820356 LEDDim 350/400/Smart White Elko Adapter				L55 x W55 x H14
 820424 LEDDim 350/400/Smart White SG Front				L83 x W83 x H23