



LED spot for under cabinet and canopy lighting. Can be both flush-mounted and surface-mounted using the removable ring. Spot incl. three-metre cable for simple connection to driver (accessory). Made of die-cast aluminium

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>970064 LEDstar Black 180lm 2700K Ra>90 2.4W LED 75 lm/W SDCM:3 L70/B50>50,000 Beam: 40°, Direct, Opal</p>	Class III IP54		Recessed or surface, Indoor Cable 3m	Ø82 x H22
 <p>997064 LEDstar Brushed steel 180lm 2700K Ra>90 2.4W LED 75 lm/W SDCM:3 L70/B50>50,000 Beam: 40°, Direct, Plastic clear</p>	Class III IP54		Recessed or surface, Indoor Cable 3m	Ø82 x H22
 <p>912064 LEDstar White 180lm 2700K Ra>90 2.4W LED 75 lm/W SDCM:3 L70/B50>50,000 Beam: 40°, Direct, Opal</p>	Class III IP54		Recessed or surface, Indoor Cable 3m	Ø82 x H22
Drivers				
 <p>820444 IP65 Junction box Black Incl driver 90W Trailing edge</p>				L346 x W127 x H53
 <p>820576 SG White Driver 24V 150W DALI-2 / Push Dim 150W 50,000</p>	Class II IP20	DALI-2 / Push Dim	Indoor	L240 x W59 x H40
 <p>820186 SG White Driver 24V 20W 24V Trailing edge</p>				L250 x W70 x H28
 <p>820440 SG White Driver 24V 36W Trailing edge</p>				L200 x W85 x H35
 <p>820441 SG White Driver 24V 75W Trailing edge</p>				L200 x W85 x H35
 <p>820442 SG White Driver 24V 150W Trailing edge</p>				L310 x W85 x H35