


DALI dimmer, which can control both the intensity and colour (via DALI Type 8). In order to change the colour temperature, simply double click on the rotary switch. The 4 buttons allow you to save the applicable setting, which can be recreated at the click of a button. It features an integrated DALI power supply that ensures simple installation without the need for any other DALI equipment. One LEDDim DALI can control up to 64 DALI luminaires via broadcast. It is possible to connect up to 4 LEDDim DALI units together and control up to 256 DALI fixtures.

LEDDim DALI











Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
Accessories				
 78501 Back box Black 1X	IP41		Surface, Indoor	L86 x W86 x H35
 78511 Back box Black 2X	IP41		Surface, Indoor	L86 x W157 x H35
 78521 Back box Black 3X	IP41		Surface, Indoor	L86 x W228 x H35
 820422 LEDDim Smart Black TW DALI Front				L54 x W54 x H13
 820480 LEDDim V5 - Black TW/MASTER/DALI SG Front				L84 x W84 x H13
 78500 Back box White 1X	IP41		Surface, Indoor	L86 x W86 x H35
 78510 Back box White 2X	IP41		Surface, Indoor	L86 x W157 x H35
 78520 Back box White 3X	IP41		Surface, Indoor	L86 x W228 x H35