

Tube Micro R



Tube Micro R is a stylish, minimalist built-in spot for installation in level or sloping ceilings. Its intense light can be used indirectly for general lighting or directly to highlight parts of the surroundings. The spot can be turned and tilted to direct the light to exactly where light is needed. Tube Micro R can be installed easily in holes in the ceiling using springs. The luminaire is ideal for refurbishments, as it fits in holes from $\text{\O}68\text{--}83$ mm. The luminaire also fits SG's Rehabrings (accessory) up to $\text{\O}250$. The driver and junction box are IsoSafe and can be installed directly into insulation. Can be looped and is Class II, which facilitates easy replacement where there is no earth lead. Tube Micro R comes as standard with a low-glare black bezel. Other bezels are available separately as accessories.

Tube Micro R



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>320755 Tube Micro R Black DimToWarm 590lm 2000-2800K Ra>95 DALI-2 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L135 x W39 x H135
 <p>320712 Tube Micro R Black DimToWarm 590lm 2000-2800K Ra>95 Trailing edge 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L39 x W39 x H135
 <p>320860 Tube Micro R Brass DimToWarm 590lm 2000-2800K Ra>95 Trailing edge 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L135 x W39 x H135
 <p>320752 Tube Micro R White DimToWarm 590lm 2000-2800K Ra>95 DALI-2 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor	L135 x W39 x H135
 <p>320709 Tube Micro R White DimToWarm 590lm 2000-2800K Ra>95 Trailing edge 12W LED 49 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L39 x W39 x H135
 <p>320753 Tube Micro R Black 680lm 2700K Ra 98 DALI-2 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L39 x W39 x H135

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>320710 Tube Micro R Black 680lm 2700K Ra 98 Trailing edge 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L39 x W39 x H135
 <p>320859 Tube Micro R Brass 680lm 2700K Ra 98 Trailing edge 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L135 x W39 x H135
 <p>320750 Tube Micro R White 680lm 2700K Ra 98 DALI-2 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L135 x W39 x H135
 <p>320707 Tube Micro R White 680lm 2700K Ra 98 Trailing edge 15W LED 45 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L39 x W39 x H135
 <p>320754 Tube Micro R Black 700lm 3000K Ra 98 DALI-2 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	L39 x W39 x H135
 <p>320711 Tube Micro R Black 700lm 3000K Ra 98 Trailing edge 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	Class II IP20	Trailing edge	Recessed, Indoor	L39 x W39 x H135

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>320751 Tube Micro R White 700lm 3000K Ra 98 DALI-2 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	<p>Class II IP20</p>	DALI-2	<p>Recessed, Indoor 5 pol Linect / screwless terminal block</p>	L135 x W39 x H135
 <p>320708 Tube Micro R White 700lm 3000K Ra 98 Trailing edge 15W LED 47 lm/W SDCM:2 L90/B10>100,000 Beam: 36°, Direct, Reflector</p>	<p>Class II IP20</p>	Trailing edge	Recessed, Indoor	L39 x W39 x H135
Accessories				
 <p>9143 Rehab Ring Black 133mm for Junistar, Uniled, Soft & Jupiter</p>				Ø133 x H4
 <p>9236 Rehab Ring Black 180mm for Junistar, Uniled, Soft & Jupiter</p>				Ø180 x H45
 <p>9427 Rehab Ring Black 250mm for Junistar, Uniled, Soft & Jupiter</p>				Ø250 x H45
 <p>320681 Tube Micro Black Ø39 Bezel</p>				Ø37 x H11
 <p>320682 Tube Micro Gold Ø39 Bezel</p>				Ø37 x H11
 <p>9234 Rehab Ring Graphite 180mm for Junistar, Uniled, Soft & Jupiter</p>				Ø180 x H45
 <p>9327 Rehab Ring Graphite 250mm for Junistar, Uniled, Soft & Jupiter</p>				Ø250 x H45
 <p>320756 Tube Micro Opal 10mm Decoration ring</p>				Ø39 x H21

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 9223 Rehab Ring White 133mm for Junistar, Uniled, Soft & Jupiter				Ø133 x H4
 9224 Rehab Ring White 180mm for Junistar, Uniled, Soft & Jupiter				Ø180 x H45
 9227 Rehab Ring White 250mm for Junistar, Uniled, Soft & Jupiter				Ø250 x H45
 320680 Tube Micro White Ø39 Bezel				Ø37 x H11