

Light sources GU10



GU10 LED dimmable light source with five-year system warranty if used together with a SG luminaire.

Light sources GU10



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 830984 GU10 Brushed steel DimToWarm 345lm 2000-2800K Ra>90 6W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 36°, Direct,		Trailing edge		L55 x W50 x H50
 830983 GU10 White DimToWarm 345lm 2000-2800K Ra>90 6W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 36°, Direct,		Trailing edge		L55 x W50 x H50
 830962 GU10 Brushed steel 360lm 2700K Ra>90 6W LED 60 lm/W SDCM:2 L70/B50>50,000 Beam: 32°, Direct,		Trailing edge		L55 x W50 x H50
 830980 GU10 Silver 450lm 2700K Ra>80 6.2W LED 73 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,		Trailing edge		L65 x W50 x H50
 830956 GU10 White 250lm 2700K Ra>80 4.5W LED 56 lm/W SDCM:4 L70/B50>40,000 Beam: 36°, Direct,		Trailing edge		L55 x W50 x H50
 830960 GU10 White 360lm 2700K Ra>90 6W LED 60 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,		Trailing edge		L55 x W50 x H50
 830985 GU10 White 270lm 2700K Ra>80 3W LED 90 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,		Trailing edge		L50 x W50 x H55

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 830981 GU10 Silver 455lm 3000K Ra>80 6.2W LED 73 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,		Trailing edge		L65 x W50 x H50
 830961 GU10 White 375lm 3000K Ra>90 6W LED 63 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,		Trailing edge		L55 x W50 x H50
 830982 GU10 Silver 480lm 4000K Ra>80 6.2W LED 77 lm/W SDCM:4 L70/B50>25,000 Beam: 36°, Direct,		Trailing edge		L65 x W50 x H50