

# Metro



Stylishly clean wall luminaire giving attractive up and down light or just down light. Replaceable light source (included). Made of powder-coated die-cast aluminium with glass diffuser, Option of either visible or concealed connection, and connectors between wall fittings and luminaire.

## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>614691  <b>Metro Black 180lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>4.5W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>614693  <b>Metro Black 360lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>9W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L160 x W90 x H215 x D147
 <p>614696  <b>Metro Black Ceiling 180lm 2700K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>4.5W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>623691  <b>Metro Graphite 180lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>4.5W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>623693  <b>Metro Graphite 360lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>9W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L160 x W90 x H215 x D147
 <p>623696  <b>Metro Graphite Ceiling 180lm</b>  <b>2700K Ra&gt;80 Trailing edge</b>  <b>4.5W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>611691  <b>Metro White 180lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>4.5W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>611693  <b>Metro White 360lm 2700K Ra&gt;80</b>  <b>Trailing edge</b>  <b>9W LED</b>            40 lm/W SDCM:4            L70/B50&gt;40,000            Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L160 x W90 x H215 x D147
 <p>624697  <b>Metro Black 330lm 3000K Ra&gt;80</b>  <b>Trailing edge</b>  <b>6.2W LED</b>            53 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>624698  <b>Metro 2x6,2W Black 660lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>12.4W LED</b>            53 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>624699  <b>Metro Black Ceiling 330lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b>            53 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>633697  <b>Metro Graphite 330lm 3000K Ra&gt;80</b>  <b>Trailing edge</b>  <b>6.2W LED</b>            53 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>633698  <b>Metro 2x6,2W Graphite 660lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>12.4W LED</b>                      53 lm/W SDCM:4                      L70/B50&gt;25,000                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>633699  <b>Metro Graphite Ceiling 330lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b>                      53 lm/W SDCM:4                      L70/B50&gt;25,000                      Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>621697  <b>Metro White 330lm 3000K Ra&gt;80</b>  <b>Trailing edge</b>  <b>6.2W LED</b>                      53 lm/W SDCM:4                      L70/B50&gt;25,000                      Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>621698  <b>Metro 2x6,2W White 660lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>12.4W LED</b>                      53 lm/W SDCM:4                      L70/B50&gt;25,000                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>621699  <b>Metro White Ceiling 330lm 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>6.2W LED</b>                      53 lm/W SDCM:4                      L70/B50&gt;25,000                      Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>633700  <b>Metro Graphite 250lm 4000K Ra&gt;80</b>  <b>Trailing edge</b>  <b>4.5W LED</b>                      56 lm/W SDCM:4                      L70/B50&gt;40,000                      Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b>  <b>IP65</b>  <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>633701  <b>Metro Graphite 500lm 4000K Ra&gt;80</b>  <b>Trailing edge</b>  <b>9W LED</b>                      56 lm/W SDCM:4                      L70/B50&gt;40,000                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>614690  <b>Metro 1x35W Black Trailing edge</b>  <b>35W LED</b>                      Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>614692  <b>Metro 2x35W Black Trailing edge</b>  <b>70W LED</b>                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>614695  <b>Metro 1x35W Black Ceiling Trailing edge</b>  <b>35W LED</b>                      Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>623690  <b>Metro 1x35W Graphite Trailing edge</b>  <b>35W LED</b>                      Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>623692  <b>Metro 2x35W Graphite Trailing edge</b>  <b>70W LED</b>                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147
 <p>623695  <b>Metro 1x35W Graphite Ceiling Trailing edge</b>  <b>35W LED</b>                      Beam: 35°, Direct, Glass Clear</p>	<b>Class I</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
 <p>611690  <b>Metro 1x35W White Trailing edge</b>  <b>35W LED</b>                      Beam: 35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H120 x D147
 <p>611692  <b>Metro 2x35W White Trailing edge</b>  <b>70W LED</b>                      Beam: 35°/35°, Direct, Glass Clear</p>	<b>Class II</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	W90 x H215 x D147

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 611695 <b>Metro 1x35W White Ceiling</b> <b>Trailing edge</b> <b>35W LED</b> Beam: 35°, Direct, Glass Clear	<b>Class I</b> <b>IP65</b> <b>IK07</b>	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø90 x H120
<b>Accessories</b>				
 614207 <b>Black Corner bracket</b>				W80 x H101 x D50
 623207 <b>Graphite Corner bracket</b>				W80 x H101 x D50
 611207 <b>White Corner bracket</b>				W80 x H101 x D50