

Langfoss Mini



Langfoss is a powerful floodlight luminaire suitable for lighting large spaces, transport and storage areas, playgrounds, courts and car parks. Can also be used as facade lighting. Nordic design for Nordic conditions. The sloping top allows snow to slide off, and the bracket can withstand heavy loads. Asymmetrical optics send the light where it is needed, and the mounting bracket can be angled as required. Super simple installation with two-piece mounting bracket with hooks. Die-cast powder-coated aluminium with tempered glass front. Accessories for flexible installation: post for mounting top, post for mounting sides, corner bracket and extension cable.

Langfoss Mini



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 641931 Langfoss Mini Graphite 8640lm 3000K Ra>70 DALI-2 68W LED 127 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Asymmetric, Lens	Class I IP66 IK07	DALI-2	Indoor / Outdoor Cable 5x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641938 Langfoss Mini Graphite 4850lm 3000K Ra>70 On/Off 35W LED 139 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetric, Lens	Class I IP66 IK07	On/Off	Indoor / Outdoor Cable 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641939 Langfoss Mini Graphite 8640lm 3000K Ra>70 On/Off 68W LED 127 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetric, Lens	Class I IP66 IK07	On/Off	Indoor / Outdoor Cable 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641933 Langfoss Mini Graphite 9330lm 4000K Ra>70 DALI-2 68W LED 137 lm/W SDCM:3 L80/B50>100,000, L90/B10>50,000 Asymmetric, Lens	Class I IP66 IK07	DALI-2	Indoor / Outdoor Cable 5x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641940 Langfoss Mini Graphite 5240lm 4000K Ra>70 On/Off 35W LED 150 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetric, Lens	Class I IP66 IK07	On/Off	Indoor / Outdoor Cable 3x1mm ² 2m, H07RN-F	L362 x W265 x H85
 641941 Langfoss Mini Graphite 9330lm 4000K Ra>70 On/Off 68W LED 137 lm/W SDCM:3 L80/B50>100,000, L94>50,000 Asymmetric, Lens	Class I IP66 IK07	On/Off	Indoor / Outdoor Cable 3x1mm ² 2m, H07RN-F	L362 x W265 x H85

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	641916 Langfoss Mini Graphite Corner bracket			L139 x W249 x H180
	641917 Langfoss Mini Ø60/76 Graphite Pole-top			L142 x W249 x H112
	641918 Langfoss Mini Ø60/76 Graphite Pole bracket			L67 x W249 x H89
	641919 Langfoss Mini Ø89/108 Graphite Pole bracket			L67 x W249 x H89
	641949 Langfoss/Mini/Maxi Graphite Fixing Plate for sandwich panels			L430 x W250 x H7
	820259 Start current limiter DIN 16A			L90 x W18 x H58