



Attractive, round LED wall/ceiling luminaire for indoor mounting. Made of painted metal. Diffuser made of UV-stabilised opal polycarbonate. Efficient LED board with long service life. Hatch for easy access to connection, and option of both visible and concealed cabling as well as loopable quick clips. Vandal-resistant rating IK10.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212105 Orion Black 760lm 2700K Ra>80 Trailing edge 8W LED 95 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H87
	212100 Orion White 770lm 2700K Ra>80 Trailing edge 8W LED 96 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H87
	212139 Orion White 1480lm 2700K Ra>80 Trailing edge 15W LED 99 lm/W SDCM:3 L70/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H87
	212113 Orion White Wireless 760lm 3000K Ra>80 On/Off 10W LED 76 lm/W SDCM:3 L70/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	On/Off	Surface, Indoor Screwless terminal block	Ø300 x H87
	212118 Orion White Wireless 1460lm 3000K Ra>80 On/Off 20W LED 73 lm/W SDCM:3 L70/B50>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	On/Off	Surface, Indoor Screwless terminal block	Ø300 x H87
	212111 Orion White 800lm 3000K Ra>80 Sensor 8W LED 100 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Sensor	Surface, Indoor Screwless terminal block	Ø300 x H87

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212134 Orion White 1510lm 3000K Ra>80 Sensor Dim 15W LED 101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Sensor Dim	Surface, Indoor Screwless terminal block	Ø300 x H87
 212112 Orion White 760lm 3000K Ra>80 Sensor Wireless 10W LED 76 lm/W SDCM:3 L70/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Sensor Wireless	Surface, Indoor Screwless terminal block	Ø300 x H87
 212117 Orion White 1350lm 3000K Ra>80 Sensor Wireless 19W LED 71 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Sensor Wireless	Surface, Indoor Screwless terminal block	Ø300 x H87
 212110 Orion White 800lm 3000K Ra>80 Trailing edge 8W LED 100 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H87
 212115 Orion White 1510lm 3000K Ra>80 Trailing edge 15W LED 101 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	Trailing edge	Surface, Indoor Screwless terminal block	Ø300 x H87
 212128 Orion White Wireless 1515lm 4000K Ra>80 On/Off 20W LED 76 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Direct, Opal	Class II IP20 IK10	On/Off	Surface, Indoor Screwless terminal block	Ø300 x H87

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	212126	Class II	Sensor	Surface, Indoor	Ø300 x H87
	Orion White 1380lm 4000K Ra>80	IP20		Screwless terminal block	
	Sensor	IK10			
	19W LED				
	73 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Direct, Opal				
	212135	Class II	Sensor Dim	Surface, Indoor	Ø300 x H87
	Orion White 1540lm 4000K Ra>80	IP20		Screwless terminal block	
	Sensor Dim	IK10			
	15W LED				
	103 lm/W SDCM:3 L80/B10>50,000 Beam: 110°, Direct, Opal				
	212127	Class II	Sensor Wireless	Surface, Indoor	Ø300 x H87
	Orion White 1515lm 4000K Ra>80	IP20		Screwless terminal block	
	Sensor Wireless	IK10			
	20W LED				
	76 lm/W SDCM:3 L70/B50>50,000 Beam: 110°, Direct, Opal				
	212125	Class II	Trailing edge	Surface, Indoor	Ø300 x H87
	Orion White 1540lm 4000K Ra>80	IP20		Screwless terminal block	
	Trailing edge	IK10			
	15W LED				
	103 lm/W SDCM:3 L80/B10>100,000, L90/B10>50,000 Beam: 110°, Direct, Opal				