









Mirror luminaire made of aluminium with diffuser made of Acrylic (PMMA). Can be installed with either with concealed or visible cable. Design: Hallvard Jakobsen

Product- and environment images









Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	197341 Prelude Brushed steel w/ outlet 890lm 2700K Ra>90 Trailing edge 14W LED 64 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
	198324 Prelude Chrome 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
	111324 Prelude White 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
	111340 Prelude White 1020lm 2700K Ra>90 Trailing edge 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
	111341 Prelude White w/ outlet 1020lm 2700K Ra>90 Trailing edge 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
	111343 Prelude White w/ 2 x outlet 1020lm 2700K Ra>90 Trailing edge 14W LED 73 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L630 x W70 x H81 x D81

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	111344 Prelude White w/ 2 x outlet 1000lm 2700K Ra>90 Trailing edge 16W LED 63 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	W630 x H70 x D80
	197345 Prelude Brushed steel 960lm 3000K Ra>90 Trailing edge 16W LED 60 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
	111345 Prelude White 1060lm 3000K Ra>90 Trailing edge 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
	111346 Prelude White w/ outlet 1060lm 3000K Ra>90 Trailing edge 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
	111347 Prelude White w/ outlet 1060lm 3000K Ra>90 Trailing edge 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	W560 x H70 x D80
	111349 Prelude White w/ 2 x outlet 1060lm 3000K Ra>90 Trailing edge 14W LED 76 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	W630 x H70 x D80