

Prelude



Mirror luminaire made of aluminium with diffuser made of Acrylic (PMMA). Can be installed with either with concealed or visible cable. Design: Hallvard Jakobsen

Prelude



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>197341 Prelude Brushed steel w/ outlet 960lm 2700K Ra>90 Trailing edge 11W LED 87 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
 <p>198324 Prelude Chrome 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal</p>	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
 <p>111324 Prelude White 2700K Ra>80 On/Off 14W Fluorescent lamp D=16 mm Direct, Opal</p>	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	On/Off	Surface, Indoor Screwless terminal block	W606 x H70 x D80
 <p>111340 Prelude White 1050lm 2700K Ra>90 Trailing edge 11W LED 95 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
 <p>111341 Prelude White w/ outlet 1050lm 2700K Ra>90 Trailing edge 11W LED 95 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
 <p>111343 Prelude White w/ 2 x outlet 1050lm 2700K Ra>90 Trailing edge 11W LED 95 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L630 x W70 x H81 x D81

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>197345 Prelude Brushed steel 960lm 3000K Ra>90 Trailing edge 16W LED 60 lm/W SDCM:3 L70/B10>50,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
 <p>111345 Prelude White 1090lm 3000K Ra>90 Trailing edge 11W LED 99 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L510 x W70 x H80 x D80
 <p>111346 Prelude White w/ outlet 1090lm 3000K Ra>90 Trailing edge 11W LED 99 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	L560 x W70 x H80 x D80
 <p>111347 Prelude White w/ outlet 1090lm 3000K Ra>90 Trailing edge 11W LED 99 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal</p>	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05	Trailing edge	Surface, Indoor Screwless terminal block	W560 x H70 x D80