

Primo



Attractive, round wall luminaire that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK10. Variants integrated sensor or Twilight relay.

Primo



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>644571 Primo 1100 Black 760lm 3000K Ra>80 Sensor 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>644570 Primo 1100 Black 760lm 3000K Ra>80 Trailing edge 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>644574 Primo 1100 Black 760lm 3000K Ra>80 Twilight 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>643571 Primo 1100 Graphite 760lm 3000K Ra>80 Sensor 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>643570 Primo 1100 Graphite 760lm 3000K Ra>80 Trailing edge 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>643574 Primo 1100 Graphite 760lm 3000K Ra>80 Twilight 8W LED 95 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>641571 Primo 1100 White 780lm 3000K Ra>80 Sensor 8W LED 98 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>641570 Primo 1100 White 780lm 3000K Ra>80 Trailing edge 8W LED 98 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>641574 Primo 1100 White 780lm 3000K Ra>80 Twilight 8W LED 98 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120
 <p>644573 Primo 1100 Black 790lm 4000K Ra>80 Sensor 8W LED 99 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D110
 <p>644572 Primo 1100 Black 790lm 4000K Ra>80 Trailing edge 8W LED 99 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D110
 <p>643572 Primo 1100 Graphite 760lm 4000K Ra>80 Trailing edge 10W LED 76 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H120 x D120

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>641573 Primo 1100 White 810lm 4000K Ra>80 Sensor 8W LED 101 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D110
 <p>641572 Primo 1100 White 810lm 4000K Ra>80 Trailing edge 8W LED 101 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D110
 <p>614570 Primo Black E27 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H135 x D120
 <p>623570 Primo Graphite E27 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H135 x D120
 <p>611570 Primo White E27 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10		Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H135 x D120

Accessories

 <p>614580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Black</p>				L1000 x W290 x H220
 <p>623580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Graphite</p>				L1000 x W290 x H220
 <p>600580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Anchoring set</p>				W330 x H524 x D260