

Rax Soft 150



Rax Soft 150 is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft 150 is installed easily with springs that fit ceiling panels with a thickness of 1-50 mm.

Rax Soft 150



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212501 Rax Soft 150 Satin 1600 3000K Ra>80 DALI-2 / Push Dim 13W LED 123 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212505 Rax Soft 150 Satin 2200 3000K Ra>80 DALI-2 / Push Dim 18W LED 119 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212507 Rax Soft 150 Satin 2200 3000K Ra>90 DALI-2 / Push Dim 22W LED 98 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212511 Rax Soft 150 Satin 3000 3000K Ra>80 DALI-2 / Push Dim 26W LED 114 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212500 Rax Soft 150 Satin 1600 3000K Ra>80 Trailing edge 13W LED 123 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83
 <p>212504 Rax Soft 150 Satin 2200 3000K Ra>80 Trailing edge 18W LED 119 lm/W SDCM:2</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector 212506 Rax Soft 150 Satin 2200 3000K Ra>90 Trailing edge 22W LED 98 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>Trailing edge</p>	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
 <p>212510 Rax Soft 150 Satin 3000 3000K Ra>80 Trailing edge 26W LED 114 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>Trailing edge</p>	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
 <p>212503 Rax Soft 150 Satin 1600 4000K Ra>80 DALI-2 / Push Dim 13W LED 127 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
 <p>212509 Rax Soft 150 Satin 2200 4000K Ra>80 DALI-2 / Push Dim 18W LED 123 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
 <p>212513 Rax Soft 150 Satin 3000 4000K Ra>80 DALI-2 / Push Dim 26W LED 118 lm/W SDCM:2 L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
 <p>212571 Rax Soft 150 Satin 2200 4000K Ra>90 DALI-2 / Push Dim 22W LED 105 lm/W SDCM:2</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>


Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>L90/B10>100,000 Beam: 68°, Direct, Satin Matt Reflector</p> <p>Rax Soft 150 Satin 1600 4000K Ra>80 Trailing edge 13W LED 127 lm/W SDCM:2 L90/B10>100,000</p>	<p>Class II SELV IP54/IP20 IK08</p>	Trailing edge	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	Ø166 x H83
 <p>212508 Beam: 68°, Direct, Satin Matt Reflector</p> <p>Rax Soft 150 Satin 2200 4000K Ra>80 Trailing edge 18W LED 123 lm/W SDCM:2 L90/B10>100,000</p>	<p>Class II SELV IP54/IP20 IK08</p>	Trailing edge	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	Ø166 x H83
 <p>212512 Beam: 68°, Direct, Satin Matt Reflector</p> <p>Rax Soft 150 Satin 3000 4000K Ra>80 Trailing edge 26W LED 118 lm/W SDCM:2 L90/B10>100,000</p>	<p>Class II SELV IP54/IP20 IK08</p>	Trailing edge	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	Ø166 x H83
 <p>212570 Beam: 68°, Direct, Satin Matt Reflector</p> <p>Rax Soft 150 Satin 2200 4000K Ra>90 Trailing edge 22W LED 105 lm/W SDCM:2 L90/B10>100,000</p>	<p>Class II SELV IP54/IP20 IK08</p>	Trailing edge	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	Ø166 x H83
Accessories				
 <p>212617 Rax 150 Black Rehabring Ø155-200mm</p>				Ø220 x H16
 <p>212621 Rax 150 Black Glass clear IP44</p>				Ø168 x H12
 <p>212623 Rax 150 Black Glass frosted IP44</p>				Ø168 x H12

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212620 Rax 150 White Glass clear IP44				Ø168 x H12
 212622 Rax 150 White Glass frosted IP44				Ø168 x H12
 820489 Sensor Dim Box White 200VA				L220 x W75 x H34
 8249044683 Rax 150 White Rehabring Ø155-200mm				Ø220 x H16
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 900109 Reliefplate Weight distribution panel				L400 x W400 x H1
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35
 8249042216 Rax 150 Mounting plate				L585 x W260 x H15