

Rax Soft 150 Asymmetric



Rax Soft in an asymmetric version for illuminating walls in corridors, offices etc. The asymmetric lens gives excellent light control and provides a conical light pattern on the wall, minimizing glare and giving a comfortable wall illumination. Rax Soft Asymmetric is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.

Rax Soft 150 Asymmetric



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212533 • Rax Soft 150 Satin Asymmetric 1600 3000K Ra>80 DALI-2 / Push Dim 15W LED 104 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212537 • Rax Soft 150 Satin Asymmetric 2200 3000K Ra>80 DALI-2 / Push Dim 22W LED 102 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212541 • Rax Soft 150 Satin Asymmetric 3000 3000K Ra>80 DALI-2 / Push Dim 30W LED 97 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212532 Rax Soft 150 Satin Asymmetric 1600 3000K Ra>80 Trailing edge 15W LED 104 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83
 <p>212536 • Rax Soft 150 Satin Asymmetric 2200 3000K Ra>80 Trailing edge 22W LED 102 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83
 <p>212540 • Rax Soft 150 Satin Asymmetric 3000 3000K Ra>80 Trailing edge 30W LED 97 lm/W SDCM:2 L90/B10>100,000</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83


Article codes



Article	Direct, Satin Matt Reflector	Protection	Control gear	Mounting/Connection	Dimensions
	<p>212535 •</p> <p>Rax Soft 150 Satin Asymmetric 1600 4000K Ra>80 DALI-2 / Push Dim 15W LED 107 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
	<p>212539 •</p> <p>Rax Soft 150 Satin Asymmetric 2200 4000K Ra>80 DALI-2 / Push Dim 22W LED 105 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
	<p>212543 •</p> <p>Rax Soft 150 Satin Asymmetric 3000 4000K Ra>80 DALI-2 / Push Dim 30W LED 100 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>DALI-2 / Push Dim</p>	<p>Recessed, Indoor Cable 5x0,75mm² 5 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
	<p>212534</p> <p>Rax Soft 150 Satin Asymmetric 1600 4000K Ra>80 Trailing edge 15W LED 107 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>Trailing edge</p>	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
	<p>212538 •</p> <p>Rax Soft 150 Satin Asymmetric 2200 4000K Ra>80 Trailing edge 22W LED 105 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>Trailing edge</p>	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
	<p>212542 •</p> <p>Rax Soft 150 Satin Asymmetric 3000 4000K Ra>80 Trailing edge 30W LED</p>	<p>Class II SELV IP54/IP20 IK08</p>	<p>Trailing edge</p>	<p>Recessed, Indoor 3 pol Linect / screwless terminal block</p>	<p>Ø166 x H83</p>
Accessories	<p>100 lm/W SDCM:2 L90/B10>100,000</p>				

Article codes



Article	Direct, Satin Matt Reflector	Protection	Control gear	Mounting/Connection	Dimensions
	212617 Rax 150 Black Rehabring Ø155-200mm				Ø220 x H16
	212621 Rax 150 Black Glass clear IP44				Ø168 x H12
	212623 Rax 150 Black Glass frosted IP44				Ø168 x H12
	212620 Rax 150 White Glass clear IP44				Ø168 x H12
	212622 Rax 150 White Glass frosted IP44				Ø168 x H12
	8249044683 Rax 150 White Rehabring Ø155-200mm				Ø220 x H16
	8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
	900109 Reliefplate Weight distribution panel				L400 x W400 x H1
	8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
	8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35
	8249042216 Rax 150 Mounting plate				L585 x W260 x H15

• = This article is produced by order, with an expected delivery time of 3-4 weeks.