

Rax Soft 150 Black





Rax Soft 150 Black is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with black reflector for excellent glare control and UGR

Rax Soft 150 Black



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212557 Rax Soft 150 Black 1600 3000K Ra>80 DALI-2 / Push Dim 15W LED 102 lm/W SDCM:2 L90/B10>100,000 Beam: 65°, Direct, Black reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212556 Rax Soft 150 Black 1600 3000K Ra>80 Trailing edge 15W LED 102 lm/W SDCM:2 L90/B10>100,000 Beam: 65°, Direct, Black reflector</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83
 <p>212559 Rax Soft 150 Black 1600 4000K Ra>80 DALI-2 / Push Dim 15W LED 105 lm/W SDCM:2 L90/B10>100,000 Beam: 65°, Direct, Black reflector</p>	Class II SELV IP54/IP20 IK08	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm ² 5 pol Linect / screwless terminal block	Ø166 x H83
 <p>212558 Rax Soft 150 Black 1600 4000K Ra>80 Trailing edge 15W LED 105 lm/W SDCM:2 L90/B10>100,000 Beam: 65°, Direct, Black reflector</p>	Class II SELV IP54/IP20 IK08	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø166 x H83
Accessories				
 <p>212617 Rax 150 Black Rehabring Ø155-200mm</p>				Ø220 x H16
 <p>212621 Rax 150 Black Glass clear IP44</p>				Ø168 x H12
 <p>212623 Rax 150 Black Glass frosted IP44</p>				Ø168 x H12
 <p>212620 Rax 150 White Glass clear IP44</p>				Ø168 x H12

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212622 Rax 150 White Glass frosted IP44				Ø168 x H12
 820489 Sensor Dim Box White 200VA				L220 x W75 x H34
 8249044683 Rax 150 White Rehabring Ø155-200mm				Ø220 x H16
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 900109 Reliefplate Weight distribution panel				L400 x W400 x H1
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35
 8249042216 Rax 150 Mounting plate				L585 x W260 x H15