

Rax 200 TW



LED downlight. Made of fire-resistant polycarbonate. SDCM 3. Supplied with tunable white 2700–6500K with DALI 8 control. Complete with driver. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector. Tunable White 2700–6500K LEDDim or DALI Type 8.

Rax 200 TW



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212309 Rax 200 TW White 2500lm 2700-6500K Ra>80 TW LEDDim 28W LED 89 lm/W SDCM:3 L90/B10>100,000 Direct, Satin Matt Reflector	Class II SELV IP20	TW LEDDim	Recessed, Indoor	Ø223
Accessories				
 212618 Rax 200 Black Rehabring Ø205-250mm				Ø270 x H16
 212619 Rax 200 Black Rehabring Ø210-280mm				Ø300 x H16
 8249045035 Rax 200 Black frontring				L224 x W24 x H10
 212628 Rax 200 White Rehabring Ø210-280mm				Ø300 x H16
 8249038725 Rax 200 Mounting plate				L585 x W260 x H15
 8249043532 • Rax 200 Mounting ring				L265 x W265 x H70
 8249044476 • Rax 200				L265 x W265 x H70

• = This article is produced by order, with an expected delivery time of 3-4 weeks.