

# Rax Soft 200 Asymmetric



Rax Soft in an asymmetric version for illuminating walls in corridors, offices etc. The asymmetric lens gives excellent light control and provides a conical light pattern on the wall, minimizing glare and giving a comfortable wall illumination. Rax Soft Asymmetric is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm.

# Rax Soft 200 Asymmetric



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212545 •  <b>Rax Soft 200 Satin Asymmetric</b>  <b>1600 3000K Ra&gt;80 DALI-2 / Push</b>  <b>Dim</b>  <b>15W LED</b>            107 lm/W SDCM:2            L90/B10&gt;100,000            Direct, Satin Matt Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212549 •  <b>Rax Soft 200 Satin Asymmetric</b>  <b>2200 3000K Ra&gt;80 DALI-2 / Push</b>  <b>Dim</b>  <b>22W LED</b>            104 lm/W SDCM:2            L90/B10&gt;100,000            Direct, Satin Matt Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212553 •  <b>Rax Soft 200 Satin Asymmetric</b>  <b>3000 3000K Ra&gt;80 DALI-2 / Push</b>  <b>Dim</b>  <b>30W LED</b>            99 lm/W SDCM:2            L90/B10&gt;100,000            Direct, Satin Matt Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212544  <b>Rax Soft 200 Satin Asymmetric</b>  <b>1600 3000K Ra&gt;80 Trailing edge</b>  <b>15W LED</b>            107 lm/W SDCM:2            L90/B10&gt;100,000            Direct, Satin Matt Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
 <p>212548 •  <b>Rax Soft 200 Satin Asymmetric</b>  <b>2200 3000K Ra&gt;80 Trailing edge</b>  <b>22W LED</b>            104 lm/W SDCM:2            L90/B10&gt;100,000            Direct, Satin Matt Reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
 <p>212552 •  <b>Rax Soft 200 Satin Asymmetric</b>  <b>3000 3000K Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            99 lm/W SDCM:2            L90/B10&gt;100,000</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93

# Article codes



Article	Direct, Satin Matt Reflector	Protection	Control gear	Mounting/Connection	Dimensions
	212547 <sup>•</sup> <b>Rax Soft 200 Satin Asymmetric</b> <b>1600 4000K Ra&gt;80 DALI-2 / Push</b> <b>Dim</b> <b>15W LED</b> 110 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
	212551 <sup>•</sup> <b>Rax Soft 200 Satin Asymmetric</b> <b>2200 4000K Ra&gt;80 DALI-2 / Push</b> <b>Dim</b> <b>22W LED</b> 108 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
	212555 <sup>•</sup> <b>Rax Soft 200 Satin Asymmetric</b> <b>3000 4000K Ra&gt;80 DALI-2 / Push</b> <b>Dim</b> <b>30W LED</b> 102 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
	212546 <i>Not released yet</i> <b>Rax Soft 200 Satin Asymmetric</b> <b>1600 4000K Ra&gt;80 Trailing edge</b> <b>Dim</b> <b>15W LED</b> 110 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector	<b>Class II SELV</b> <b>IP44/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
	212550 <sup>•</sup> <b>Rax Soft 200 Satin Asymmetric</b> <b>2200 4000K Ra&gt;80 Trailing edge</b> <b>Dim</b> <b>22W LED</b> 108 lm/W SDCM:2 L90/B10>100,000 Direct, Satin Matt Reflector	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
	212554 <sup>•</sup> <b>Rax Soft 200 Satin Asymmetric</b> <b>3000 4000K Ra&gt;80 Trailing edge</b> <b>Dim</b> <b>30W LED</b>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
<b>Accessories</b>	102 lm/W SDCM:2 L90/B10>100,000				

# Article codes



Article	Direct, Satin Matt Reflector	Protection	Control gear	Mounting/Connection	Dimensions
	212618 <b>Rax 200 Black Rehabring Ø205-250mm</b>				Ø270 x H16
	212619 <b>Rax 200 Black Rehabring Ø210-280mm</b>				Ø300 x H16
	212625 <b>Rax 200 Black Glass clear IP44</b>				Ø218 x H12
	212627 <b>Rax 200 Black Glass frosted IP44</b>				Ø220 x H12
	212624 <b>Rax 200 White Glass clear IP44</b>				Ø218 x H12
	212626 <b>Rax 200 White Glass frosted IP44</b>				Ø218 x H12
	8249044696 <b>Rax 200 White Rehabring Ø205-250mm</b>				Ø270 x H16
	8246094429 <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b>				L270 x W75 x H35
	900109 <b>Reliefplate Weight distribution panel</b>				L400 x W400 x H1
	8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
	8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35
	8249038725 <b>Rax 200 Mounting plate</b>				L585 x W260 x H15

• = This article is produced by order, with an expected delivery time of 3-4 weeks.