

# Rax Soft 200 Black



Rax Soft 200 Black is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with black reflector for excellent glare control and UGR

# Rax Soft 200 Black



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212561  <b>Rax Soft 200 Black 2200 3000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>22W LED</b>            104 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212565  <b>Rax Soft 200 Black 3000 3000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            99 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212560  <b>Rax Soft 200 Black 2200 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>22W LED</b>            104 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
 <p>212564  <b>Rax Soft 200 Black 3000 3000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            99 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
 <p>212563  <b>Rax Soft 200 Black 2200 4000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>22W LED</b>            108 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93
 <p>212567  <b>Rax Soft 200 Black 3000 4000K</b>  <b>Ra&gt;80 DALI-2 / Push Dim</b>  <b>30W LED</b>            102 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	DALI-2 / Push Dim	Recessed, Indoor Cable 5x0,75mm <sup>2</sup> 5 pol Linect / screwless terminal block	Ø216 x H93


# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212562  <b>Rax Soft 200 Black 2200 4000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>22W LED</b>            108 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
 <p>212566  <b>Rax Soft 200 Black 3000 4000K</b>  <b>Ra&gt;80 Trailing edge</b>  <b>30W LED</b>            102 lm/W SDCM:2            L90/B10&gt;100,000            Beam: 63°, Direct, Black reflector</p>	<b>Class II SELV</b> <b>IP54/IP20</b> <b>IK08</b>	Trailing edge	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø216 x H93
<b>Accessories</b>				
 <p>212618  <b>Rax 200 Black Rehabring Ø205-250mm</b></p>				Ø270 x H16
 <p>212619  <b>Rax 200 Black Rehabring Ø210-280mm</b></p>				Ø300 x H16
 <p>212625  <b>Rax 200 Black Glass clear IP44</b></p>				Ø218 x H12
 <p>212627  <b>Rax 200 Black Glass frosted IP44</b></p>				Ø220 x H12
 <p>212624  <b>Rax 200 White Glass clear IP44</b></p>				Ø218 x H12
 <p>212626  <b>Rax 200 White Glass frosted IP44</b></p>				Ø218 x H12
 <p>212628  <b>Rax 200 White Rehabring Ø210-280mm</b></p>				Ø300 x H16
 <p>820489  <b>Sensor Dim Box White 200VA</b></p>				L220 x W75 x H34

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249044696 <b>Rax 200 White Rehabling Ø205-250mm</b>				Ø270 x H16
 8246094429 <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b>				L270 x W75 x H35
 900109 <b>Reliefplate Weight distribution panel</b>				L400 x W400 x H1
 8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8249038725 <b>Rax 200 Mounting plate</b>				L585 x W260 x H15