

Sense Opalprism TW 300x1200



The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldtekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in Tunable White 2700-6500K LEDDim or DALI Type 8 depending on whichever driver kit is selected (accessory).

Sense Opalprism TW 300x1200



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212316 Sense TW 300x1200 White Opalprism 4000lm 2700-6500K Ra>80 LED SDCM:3 L80/B20>50,000 Beam: 84°, Direct, Opalprism	Class III		Recessed, Indoor Quick connector	L1197 x W297 x H44
Drivers				
 820239 Sense TW Driver White 4000lm 38W TW DALI Type 8 38W	Class II	TW DALI Type 8	Indoor 5 pol Lineet / screwless terminal block	L215 x W70 x H32
 820093 Sense TW White 4000lm 40W TW LEDDim 40W	Class II	TW LEDDim IP20	Indoor 3 pol Lineet / screwless terminal block	
Accessories				
 212937 Sense 300x1200 Black Plaster board/Troldtekt Recessed frame				L1240 x W340 x H50
 212257 Sense 300x1200 White Surface frame				L1203 x W303 x H47
 8249044502 300x1200 White Plaster board/Troldtekt Recessed frame				L325 x W1225 x H55
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 212170 Sense 2m Wire kit				L2000
 212177 Sense 600x600 Asymmetric Bracket				L44 x W5 x H2.5

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	8246094364	Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours		L270 x W75 x H35
	8246094500	Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours		L270 x W75 x H35