

Sense Eco Opalprism



The Sense Eco panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency. Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Trolldtekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available with phase-dimming or DALI depending on which driver kit is selected (accessory).

Sense Eco Opalprism



Product- and environment images



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|--|--|--|-------------------|
|  <p>212222 Sense ECO 600x600 White Opalprism 3000K Ra>80 LED SDCM:3 L80/B20>50,000, L90>50,000 Beam: 110°, Direct, Opalprism</p> | <p>Class III IP40/IP20 IK10</p> | | <p>Recessed, Indoor Quick connector</p> | L595 x W595 x H10 |
|  <p>212223 Sense ECO 600x600 White Opalprism 4000K Ra>80 LED SDCM:3 L80/B20>50,000, L90>50,000 Beam: 110°, Direct, Opalprism</p> | <p>Class III IP40/IP20 IK10</p> | | <p>Recessed, Indoor Quick connector</p> | L595 x W595 x H10 |
| Drivers | | | | |
|  <p>820083 Sense Driver White 3000lm 25W 700mA DALI-2 / Push Dim 25W 100,000</p> | <p>Class II IP20</p> | <p>DALI-2 / Push Dim</p> | <p>Recessed, Indoor 5 pol Linect / screwless terminal block</p> | L124 x W79 x H22 |
|  <p>820490 Sense Driver White 3000lm 25W 700mA Trailing edge 25W 100,000</p> | <p>Class II IP20</p> | <p>Trailing edge</p> | <p>Recessed, Indoor Cable 2m Includes cable and plug</p> | L108 x W53 x H30 |
|  <p>820491 Sense Driver White 3000lm 25W 700mA Trailing edge / Linect 25W 100,000</p> | <p>Class II IP20</p> | <p>Trailing edge / Linect</p> | <p>Recessed, Indoor 3 pol Linect / screwless terminal block</p> | L108 x W53 x H30 |
| Accessories | | | | |
|  <p>212936 Sense 600x600 Black Plaster board/Troidtekt Recessed frame</p> | | | | L640 x W640 x H50 |
|  <p>212256 Sense 600x600 White Surface frame</p> | | | | L604 x W604 x H48 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|------------|--------------|---------------------|------------------|
|  820489 Sensor Dim Box White 200VA | | | | L220 x W75 x H34 |
|  8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours | | | | L270 x W75 x H35 |
|  212170 Sense 2m Wire kit | | | | L2000 |
|  212176 Sense 600x600 Concealed grid Bracket | | | | L44 x W65 x H18 |
|  212177 Sense 600x600 Asymmetric Bracket | | | | L44 x W5 x H2.5 |
|  8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours | | | | L270 x W75 x H35 |
|  8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours | | | | L270 x W75 x H35 |