

# Sense Round



Sense luminaire used as replacement or alternative for a normal downlight. Very low profile and quick connection between luminaire and driver as well as tool-free connection in junction box with loop for easy and quick installation. High efficiency up to 122lm/W and low glare rating makes Sense the obvious choice in many applications.

# Sense Round



## Product- and environment images



# Article codes



| Article                                                                             |                                                                                                                                                                                | Protection                                              | Control gear      | Mounting/Connection                                            | Dimensions |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|-------------------|----------------------------------------------------------------|------------|
|    | 212265<br><b>Sense White 190 IsoSafe 650lm</b><br><b>2700K Ra&gt;80 DALI-2 / Push Dim</b><br><b>6.5W LED</b><br>100 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø190 x H25 |
|    | 212275<br><b>Sense White 255 IsoSafe 1350lm</b><br><b>2700K Ra&gt;80 DALI-2 / Push Dim</b><br><b>12W LED</b><br>113 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø255 x H25 |
|    | 212285<br><b>Sense White 320 IsoSafe 1810lm</b><br><b>2700K Ra&gt;80 DALI-2 / Push Dim</b><br><b>16W LED</b><br>113 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø320 x H25 |
|  | 212260<br><b>Sense White 190 IsoSafe 730lm</b><br><b>2700K Ra&gt;80 Trailing edge</b><br><b>6.5W LED</b><br>112 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø190 x H25 |
|  | 212270<br><b>Sense White 255 IsoSafe 1350lm</b><br><b>2700K Ra&gt;80 Trailing edge</b><br><b>12W LED</b><br>113 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø255 x H25 |
|  | 212280<br><b>Sense White 320 IsoSafe 1810lm</b><br><b>2700K Ra&gt;80 Trailing edge</b><br><b>16W LED</b><br>113 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø320 x H25 |

# Article codes



| Article                                                                             |                                                                                                                                                                                | Protection                                              | Control gear      | Mounting/Connection                                         | Dimensions |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|-------------------|-------------------------------------------------------------|------------|
|    | 212730<br><b>Sense Black 190 IsoSafe 750lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>6.5W LED</b><br>115 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>Screwless terminal block                | Ø190 x H25 |
|    | 212731<br><b>Sense Black 255 IsoSafe 1350lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>12W LED</b><br>113 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>Screwless terminal block                | Ø255 x H25 |
|    | 212732<br><b>Sense Black 320 IsoSafe 1850lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>16W LED</b><br>116 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>Screwless terminal block                | Ø320 x H25 |
|   | 212733<br><b>Sense Black 495 3680lm 3000K</b><br><b>Ra&gt;80 Trailing edge</b><br><b>31W LED</b><br>119 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal             | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>Screwless terminal block                | Ø495 x H29 |
|  | 212266<br><b>Sense White 190 IsoSafe 670lm</b><br><b>3000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>6.5W LED</b><br>103 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal block | Ø190 x H25 |
|  | 212276<br><b>Sense White 255 IsoSafe 1370lm</b><br><b>3000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>12W LED</b><br>114 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal block | Ø255 x H25 |

# Article codes



| Article                                                                             |                                                                                                                                                                                | Protection                                              | Control gear      | Mounting/Connection                                            | Dimensions |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|-------------------|----------------------------------------------------------------|------------|
|    | 212286<br><b>Sense White 320 IsoSafe 1900lm</b><br><b>3000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>16W LED</b><br>119 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø320 x H25 |
|     | 212296<br><b>Sense White 495 3660lm 3000K</b><br><b>Ra&gt;80 DALI-2 / Push Dim</b><br><b>31W LED</b><br>118 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal         | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø495 x H29 |
|    | 212261<br><b>Sense White 190 IsoSafe 750lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>6.5W LED</b><br>115 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø190 x H25 |
|  | 212271<br><b>Sense White 255 IsoSafe 1370lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>12W LED</b><br>114 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø255 x H25 |
|  | 212281<br><b>Sense White 320 IsoSafe 1900lm</b><br><b>3000K Ra&gt;80 Trailing edge</b><br><b>16W LED</b><br>119 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø320 x H25 |
|   | 212291<br><b>Sense White 495 3660lm 3000K</b><br><b>Ra&gt;80 Trailing edge</b><br><b>31W LED</b><br>118 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal             | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø495 x H29 |




# Article codes



| Article                                                                             |                                                                                                                                                                                | Protection                                              | Control gear      | Mounting/Connection                                            | Dimensions |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|-------------------|----------------------------------------------------------------|------------|
|    | 212268<br><b>Sense White 190 IsoSafe 700lm</b><br><b>4000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>6.5W LED</b><br>108 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø190 x H25 |
|    | 212272<br><b>Sense White 255 IsoSafe 1420lm</b><br><b>4000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>12W LED</b><br>118 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø255 x H25 |
|    | 212287<br><b>Sense White 320 IsoSafe 1940lm</b><br><b>4000K Ra&gt;80 DALI-2 / Push Dim</b><br><b>16W LED</b><br>121 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø320 x H25 |
|   | 212297<br><b>Sense White 495 3760lm 4000K</b><br><b>Ra&gt;80 DALI-2 / Push Dim</b><br><b>31W LED</b><br>121 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal         | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | DALI-2 / Push Dim | Recessed, Indoor<br>5 pol Linect / screwless terminal<br>block | Ø495 x H29 |
|  | 212267<br><b>Sense White 190 IsoSafe 790lm</b><br><b>4000K Ra&gt;80 Trailing edge</b><br><b>6.5W LED</b><br>122 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø190 x H25 |
|  | 212269<br><b>Sense White 255 IsoSafe 1420lm</b><br><b>4000K Ra&gt;80 Trailing edge</b><br><b>12W LED</b><br>118 lm/W SDCM:3<br>L80/B20>100,000, L90>50,000<br>Direct, Opal     | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge     | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø255 x H25 |

# Article codes



| Article                                                                                                                                                                                                                                                                                                                                           | Protection                                              | Control gear  | Mounting/Connection                                            | Dimensions       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|---------------|----------------------------------------------------------------|------------------|
|  <p>212282<br/> <b>Sense White 320 IsoSafe 1940lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>16W LED</b><br/>                     121 lm/W SDCM:3<br/>                     L80/B20&gt;100,000, L90&gt;50,000<br/>                     Direct, Opal</p> | <b>Class II SELV</b><br><b>IP54/IP20</b><br><b>IK08</b> | Trailing edge | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø320 x H25       |
|  <p>212292<br/> <b>Sense White 495 3760lm 4000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>31W LED</b><br/>                     121 lm/W SDCM:3<br/>                     L80/B20&gt;100,000, L90&gt;50,000<br/>                     Direct, Opal</p>          | <b>Class II SELV</b><br><b>IP40/IP20</b><br><b>IK08</b> | Trailing edge | Recessed, Indoor<br>3 pol Linect / screwless terminal<br>block | Ø495 x H29       |
| <b>Accessories</b>                                                                                                                                                                                                                                                                                                                                |                                                         |               |                                                                |                  |
|  <p>820489<br/> <b>Sensor Dim Box White 200VA</b></p>                                                                                                                                                                                                             |                                                         |               |                                                                | L220 x W75 x H34 |
|  <p>8246094429<br/> <b>Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours</b></p>                                                                                                                                                                  |                                                         |               |                                                                | L270 x W75 x H35 |
|  <p>900109<br/> <b>Reliefplate Weight distribution panel</b></p>                                                                                                                                                                                                |                                                         |               |                                                                | L400 x W400 x H1 |
|  <p>8246094364<br/> <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b></p>                                                                                                                                                              |                                                         |               |                                                                | L270 x W75 x H35 |
|  <p>8246094500<br/> <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b></p>                                                                                                                                                                  |                                                         |               |                                                                | L270 x W75 x H35 |