




The Sense Eco is well designed and only 10 mm high. Narrow frame ensures attractive look and high efficiency. This makes Sense Eco an all-round quality panel that can be used everywhere. With opal prismatic diffuser, which is almost glare-free, UGR

Product- and environment images





Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212221 Sense ECO 600x600 White 2700lm 4000K 27W LED 100 lm/W SDCM:3 L80/B20>50,000, L90>50,000 Beam: 110°, Direct, Opal	Class III IP40/IP20 IK10		Recessed, Indoor Quick connector	L597 x W597 x H10
Drivers				
 820083 Sense Driver White 3000lm 25W 700mA DALI-2 / Push Dim 25W 100,000	Class II IP20	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L124 x W79 x H22
 820490 Sense Driver White 3000lm 25W 700mA Trailing edge 25W 100,000	Class II IP20	Trailing edge	Recessed, Indoor Cable 2m Includes cable and plug	L108 x W53 x H30
 820491 Sense Driver White 3000lm 25W 700mA Trailing edge / Linect 25W 100,000	Class II IP20	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	L108 x W53 x H30
Accessories				
 212936 Sense 600x600 Black Plaster board/Troldtekt Recessed frame				L640 x W640 x H50
 212256 Sense 600x600 White Surface frame				L604 x W604 x H48
 212688 Sense Decor Sky White 600x600 Frame				L597 x W597 x H79
 212780 Sense Decor Soft White 600x600 Frame				L595 x W595 x H17

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 212170 Sense 2m Wire kit				L2000
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35