



Sense Air has a thin, slimmed profile which gives an illusory floating effect in the room. The frame comes in matte white powder-coated aluminium. The Prisma diffuser creates a dazzle-free illumination and is a perfect luminaire for offices and conference rooms. The ceiling mount allows for surface-mounted fitting with either hidden or visible cabling. It is also possible to insert the ceiling mount in standard 600 × 600 inner ceilings. The low voltage current in the wires from the ceiling mount allows for an elegant solution without any visible electrical cables. The DIP switch on the driver means that the light level can be adjusted if necessary. Available with optional emergency lighting.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212241 Sense Air White 3500lm 3000K Ra>80 DALI-2 / Push Dim 36W LED 97 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	Class I IP20	DALI-2 / Push Dim	Suspended, Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13
 <p>212240 Sense Air White 3500lm 3000K Ra>80 On/Off 36W LED 97 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	Class I IP20	On/Off	Suspended, Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13
 <p>212245 • Sense Air White 3600lm 4000K Ra>80 DALI Emergency 3H 36W LED 100 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	Class I IP20	DALI Emergency 3H	Suspended, Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13
 <p>212243 Sense Air White 3600lm 4000K Ra>80 DALI-2 / Push Dim 36W LED 100 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	IP20	DALI-2 / Push Dim	Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13
 <p>212244 • Sense Air White 3600lm 4000K Ra>80 Emergency 3H/trailing edge 36W LED 100 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	Class I IP20	Emergency 3H/trailing edge	Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13
 <p>212242 Sense Air White 3600lm 4000K Ra>80 On/Off 36W LED 100 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Direct/Indirect 70/30%, Opalprism</p>	Class I IP20	On/Off	Suspended, Indoor 2x2m wire kit Screwless terminal block	L1200 x W210 x H13

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 820307 Emergency battery 3 Hours 3.0Ah - Model No: B093				L137 x W27 x H27

• = This article is produced by order, with an expected delivery time of 3-4 weeks.