

Sense Pro PIR




The Sense Pro PIR comes complete with driver, PIR sensor, cable and plug. The PIR sensor is discreetly located at the edge of the frame. The light is activated by movement and turns off automatically after a predetermined period of time to provide good energy savings. The sensor does not detect movement through walls or doors. The PIR sensor also has an adjustable daylight sensor, so you can choose not to turn on lighting when there is sufficient daylight. Sense PIR can act as a master, controlling up to 3 other Sense panels (slaves). Sense Opalprism PIR can be mounted on ceilings with visible T-rails without accessories and on ceilings with concealed T-rails with accessories.

Sense Pro PIR



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212323 Sense Opalprism 300x1200 White 3880lm 3000K Ra>80 PIR Sensor 34W LED 114 lm/W SDCM:3 L80/B20>100,000 Opalprism</p>	Class II IP20 IK10	PIR Sensor	Recessed, Indoor Cable 2m Includes driver, cable and plug	L1197 x W297 x H44
 <p>212680 Sense Pro 600x600 White 4340lm 3000K Ra>80 PIR Sensor 35W LED 124 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 110°, Direct, Opalprism</p>	Class II IP40/IP20 IK06	PIR Sensor	Recessed Cable 2m Includes driver, cable and plug	L597 x W597 x H44
 <p>212324 Sense Opalprism 300x1200 White 4060lm 4000K Ra>80 PIR Sensor 34W LED 119 lm/W SDCM:3 L80/B20>100,000 Opalprism</p>	Class II IP20 IK10	PIR Sensor	Recessed, Indoor Cable 2m Includes driver, cable and plug	L1197 x W297 x H44
 <p>212681 Sense Pro 600x600 White 4610lm 4000K Ra>80 PIR Sensor 35W LED 132 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 110°, Direct, Opalprism</p>	Class II IP40/IP20 IK06	PIR Sensor	Recessed Cable 2m Includes driver, cable and plug	L597 x W597 x H44
Accessories				
 <p>212936 Sense 600x600 Black Plaster board/Troldtekt Recessed frame</p>				L640 x W640 x H50
 <p>212256 Sense 600x600 White Surface frame</p>				L604 x W604 x H48
 <p>212257 Sense 300x1200 White Surface frame</p>				L1203 x W303 x H47
 <p>212170 Sense 2m Wire kit</p>				L2000

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212176 Sense 600x600 Concealed grid Bracket				L44 x W65 x H18
 212177 Sense 600x600 Asymmetric Bracket				L44 x W5 x H2.5