

Sense Basic 300x600



The Sense Basic 300x600 LED panel is ideal both for new installations and remodelling projects. It can directly replace 2x14W T5 and 2x18W T8 luminaires. It has a lightweight steel housing and is based on backlight, yet it is only 35 mm height. High quality non-yellowing PMMA micro prismatic front optics. Easy tool-free installation, twist connector between driver and panel and junction box with automatic strain relief for cables or plastic tubing.

Sense Basic 300x600



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212146 Sense Basic 300x600 White 2180lm 3000K Ra>80 On/Off 20W LED 109 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II IP20 IK06	On/Off	Indoor 3 pol Linect / screwless terminal block	L595 x W295 x H36
 212147 Sense Basic 300x600 White 2220lm 4000K Ra>80 On/Off 20W LED 111 lm/W SDCM:3 L80/B20>100,000 Direct, Opalprism	Class II IP20 IK06	On/Off	Indoor 3 pol Linect / screwless terminal block	L595 x W295 x H36
Accessories				
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35