



Attractive, square luminaire with direct and indirect light that can be mounted to both walls and ceilings, and both indoors and outdoors. Made of die-cast powder-coated aluminium. Flat diffuser with indirect light made of UV-stabilised opal polycarbonate. Several light source variants and sensors, and wireless control. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable terminal block. IP65 and vandal-resistant rating IK10.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	623839 Sidewalk 2000 Graphite 1250lm 3000K Ra>80 On/Off 19W LED 66 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP65 IK10	On/Off	Surface, Indoor / Outdoor Screwless terminal block	L300 x W300 x H87
	633839 Sidewalk 2000 Graphite 1300lm 3000K Ra>80 Sensor 14W LED 93 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L300 x W300 x H87
	644832 Sidewalk 2000 Black 1380lm 4000K Ra>80 Trailing edge 14W LED 99 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L300 x W300 x H87
	643833 Sidewalk 2000 Graphite 1500lm 4000K Ra>80 Sensor 14W LED 107 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L300 x W300 x H87
	643832 Sidewalk 2000 Graphite 1500lm 4000K Ra>80 Trailing edge 14W LED 107 lm/W SDCM:3 L70/B50>100,000 Beam: 110°, Direct, Opal	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L300 x W300 x H87