

SlimLine DimToWarm



SlimLine DimToWarm is an ultra-thin LED rail system where the rails can be connected no matter their size. Various accessories are available for getting around corners etc. SlimLine DimToWarm is connected to the associated drivers (accessory) Large lumen output, light beam angle and perfect colour rendering makes SlimLine DimToWarm usable in many different applications. Slimline DimToWarm is dimmable depending on which driver is selected. A connecting cable is included for all drivers.

SlimLine DimToWarm













Product- and environment images






Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>391220 SlimLine 270 White DimToWarm 260lm 2000-2800K Ra>90 5W LED 52 lm/W SDCM:5 L70/B50>50,000 Beam: 110°, Direct, Opal</p>	Class III IP20		Surface, Indoor	L270 x W17 x H7
Drivers				
 <p>820063 SlimLine White Driver 20W 24V 1-10V / Push Dim</p>				L250 x W70 x H28
 <p>820576 SG White Driver 24V 150W DALI-2 / Push Dim 150W 50,000</p>	Class II IP20	DALI-2 / Push Dim	Indoor	L240 x W59 x H40
Accessories				
 <p>391291 SlimLine Black PIR Sensor</p>		PIR Sensor	Surface, Indoor	L74 x W17 x H15
 <p>391293 SlimLine Black Switch</p>				L60 x W17 x H18
 <p>391290 SlimLine White PIR Sensor</p>		PIR Sensor	Surface, Indoor	L74 x W17 x H15
 <p>391210 SlimLine White L Connector</p>				L25 x W25 x H5
 <p>391211 SlimLine White T Connector</p>				L30 x W25 x H15
 <p>391213 SlimLine White Connector</p>				L25 x W15 x H5
 <p>391292 SlimLine White Switch</p>				L60 x W17 x H18

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 391212 SlimLine 50mm Flexible Connector				L105 x W17 x H7
 391214 SlimLine Fastening				
 391215 SlimLine Connection cable 3000mm				L120 x W100 x H26