

Soft IsoSafe DimToWarm



Attractive downlight for indoor and outdoor use. Mounted directly in insulation. Well integrated LED chip with DimToWarm chip, dimmable via phase-dimming or DALI driver. It includes a junction box that provides strain relief for several types of cables, as well as fixation for plastic tubing. Our IsoSafe products can be mounted directly in insulation (IsoSafe).

Soft IsoSafe DimToWarm



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>903223 Soft IsoSafe DimToWarm Black 470lm 2000-2800K Ra 98 Trailing edge / Linect 8W LED 59 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear</p>	Class II SELV IP54	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
 <p>903231 Soft IsoSafe DimToWarm White 550lm 2000-2800K Ra 98 DALI-2 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear</p>	Class II IP54	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
 <p>903221 Soft IsoSafe DimToWarm White 550lm 2000-2800K Ra 98 Trailing edge / Linect 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear</p>	Class II SELV IP54	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
Accessories				
 <p>9143 Rehab Ring Black 133mm for Junistar, Uniled, Soft & Jupiter</p>				Ø133 x H4
 <p>9236 Rehab Ring Black 180mm for Junistar, Uniled, Soft & Jupiter</p>				Ø180 x H45
 <p>9223 Rehab Ring White 133mm for Junistar, Uniled, Soft & Jupiter</p>				Ø133 x H4
 <p>9224 Rehab Ring White 180mm for Junistar, Uniled, Soft & Jupiter</p>				Ø180 x H45
 <p>9227 Rehab Ring White 250mm for Junistar, Uniled, Soft & Jupiter</p>				Ø250 x H45