



Attractive exclusive downlight for indoor and outdoor use (gold only for indoor use), particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium, glass diffuser. 42° beam angle. Low recessed downlight with hole size Ø83mm. Our IsoSafe products can be mounted directly in insulation (IsoSafe).

Soft Slim



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 903226 Soft Slim Black DimToWarm 490lm 2000-2800K Ra>95 Trailing edge 8W LED 61 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
 903224 Soft Slim White DimToWarm 550lm 2000-2800K Ra>95 DALI-2 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø90 x H52
 903216 Soft Slim White DimToWarm 550lm 2000-2800K Ra>95 Trailing edge 8W LED 69 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903225 Soft Slim Black 740lm 2700K Ra 98 DALI-2 11W LED 67 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø90 x H52
 903217 Soft Slim Black 740lm 2700K Ra 98 Trailing edge / Linect 11W LED 67 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903232 Soft Slim Gold 810lm 2700K Ra 98 DALI-2 11W LED 74 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor Screwless terminal block	Ø90 x H52


Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 903234 Soft Slim Gold 810lm 2700K Ra 98 Trailing edge / Linect 11W LED 74 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge / Linect	Recessed, Indoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903230 Soft Slim White 830lm 2700K Ra 98 DALI-2 11W LED 75 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø90 x H52
 903214 Soft Slim White 830lm 2700K Ra 98 Trailing edge / Linect 11W LED 75 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903238 Soft Slim Black 760lm 3000K Ra 98 DALI-2 11W LED 69 lm/W SDCM:3 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
 903243 Soft Slim Black 760lm 3000K Ra 98 Trailing edge / Linect 11W LED 69 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903222 Soft Slim White 850lm 3000K Ra 98 DALI-2 11W LED 77 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø90 x H52



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 903215 Soft Slim White 850lm 3000K Ra 98 Trailing edge 11W LED 77 lm/W SDCM:2 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø90 x H52
 903239 Soft Slim Black 790lm 4000K Ra 98 DALI-2 11W LED 72 lm/W SDCM:3 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
 903237 Soft Slim Black 790lm 4000K Ra 98 Trailing edge 11W LED 72 lm/W SDCM:3 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
 903277 Soft Slim White 880lm 4000K Ra 98 DALI-2 11W LED 80 lm/W SDCM:3 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	DALI-2	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
 903240 Soft Slim White 880lm 4000K Ra 98 Trailing edge 11W LED 80 lm/W SDCM:3 L90/B10>100,000 Beam: 42°, Direct, Reflector	Class II SELV IP54/IP20	Trailing edge	Recessed, Indoor / Outdoor Screwless terminal block	Ø90 x H52
Accessories				
 8246094429 Emergencybox Driver DALI / EM Self test, DALI Emergency 3 hours				L270 x W75 x H35
 820090 Emergencybox Adapter kit for downlight				L250 x W13 x H13

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 8246094364 Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours				L270 x W75 x H35
 8246094500 Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours				L270 x W75 x H35