



Design: Hallvard Jakobsen. Attractive, round wall luminaire with cross that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Several variants with integrated sensor or dimming relay. IP65 and vandal-resistant rating IK10.

Solo



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>644550 Solo 1100 Black 590lm 3000K Ra>80 Trailing edge 8W LED 74 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>644554 Solo 1100 Black 590lm 3000K Ra>80 Twilight 8W LED 74 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>643551 • Solo 1100 Graphite 590lm 3000K Ra>80 Sensor 8W LED 74 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>643550 Solo 1100 Graphite 590lm 3000K Ra>80 Trailing edge 8W LED 74 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>643554 Solo 1100 Graphite 590lm 3000K Ra>80 Twilight 8W LED 74 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>641551 Solo 1100 White 690lm 3000K Ra>80 Sensor 8W LED 86 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>641550 Solo 1100 White 690lm 3000K Ra>80 Trailing edge 8W LED 86 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>641554 Solo 1100 White 690lm 3000K Ra>80 Twilight 8W LED 86 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H130 x D130
 <p>643552 Solo 1100 Graphite 610lm 4000K Ra>80 Trailing edge 8W LED 76 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
Accessories				
 <p>614580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Black</p>				L1000 x W290 x H220
 <p>623580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Graphite</p>				L1000 x W290 x H220
 <p>600580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Anchoring set</p>				W330 x H524 x D260

• = This article is produced by order, with an expected delivery time of 3-4 weeks.