

Spike



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V outlet concealed behind two tip-up lids with automatic closure. If you choose the version with outlet, there is a separate terminal block for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting.

Spike



Product- and environment images



Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|--|---------------|--|------------------------------|
|  <p>623930 Spike Graphite 840lm 2700K Ra>80 Trailing edge 10W LED 84 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623931 Spike Graphite w/ outlet 840lm 2700K Ra>80 Trailing edge 10W LED 84 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623933 Spike Graphite Uplight 890lm 2700K Ra>80 Trailing edge 16W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623934 Spike Graphite Uplight w/ outlet 890lm 2700K Ra>80 Trailing edge 16W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>614910 Spike Black 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>614911 Spike Black w/ outlet 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|--|---------------|--|---------------------------|
|  <p>614912 • Spike Black w/ outlet (Type E) 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>614913 Spike Black Uplight 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>614914 Spike Black Uplight w/ outlet 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>614915 • Spike Black Uplight w/ outlet (Type E) 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>614920 Spike Black 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>614921 Spike Black w/ outlet 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|--|---------------|--|------------------------------|
|  <p>614923 Spike Black Uplight 890lm 3000K Ra>80 Twilight 17W LED 52 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>614924 Spike Black Uplight w/ outlet 890lm 3000K Ra>80 Twilight 17W LED 52 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623910 Spike Graphite 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>623911 Spike Graphite w/ outlet 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>623912 Spike Graphite w/ outlet (Type E) 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>623913 Spike Graphite Uplight 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|---------------|--|------------------------------|
|  <p>623914 Spike Graphite Uplight w/ outlet 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>623915 Spike Graphite Uplight w/ outlet (Type E) 930lm 3000K Ra>80 Trailing edge 16W LED 58 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  <p>623920 Spike Graphite 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623921 Spike Graphite w/ outlet 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal</p> | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623923 Spike Graphite Uplight 890lm 3000K Ra>80 Twilight 17W LED 52 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent</p> | Class I IP44 IK06 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  <p>623924 Spike Graphite Uplight w/ outlet 890lm 3000K Ra>80 Twilight 17W LED 52 lm/W SDCM:3 L70/B50>50,000</p> | Class I IP44 IK06 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |

Article codes



| Article | Beam: 95° down / 15° up, Direct, Plastic opal/transparent | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|--|---------------|--|---------------------------|
|  | 611915 Spike White Uplight w/ outlet (Type E) 960lm 3000K Ra>80 On/Off 16W LED 60 lm/W SDCM:3 L70/B50>50,000 Beam: 95° down / 15° up, Direct, Plastic opal/transparent | Class I IP44 IK06 | On/Off | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  | 611910 Spike White 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  | 611911 Spike White w/ outlet 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  | 611912 Spike White w/ outlet (Type E) 880lm 3000K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  | 611920 Spike White 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |
|  | 611921 Spike White w/ outlet 840lm 3000K Ra>80 Twilight 11W LED 76 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Twilight | Surface, Outdoor Screwless terminal block | L180 x W171 x H173 x D155 |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|--|---------------|--|--------------------|
|  623936 Spike Graphite 900lm 4000K Ra>80 Trailing edge 10W LED 90 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
|  623937 Spike Graphite w/ outlet 900lm 4000K Ra>80 Trailing edge 10W LED 90 lm/W SDCM:3 L70/B50>50,000 Beam: 95°, Direct, Opal | Class I IP44 IK08 | Trailing edge | Surface, Outdoor Screwless terminal block | W171 x H173 x D155 |
| Accessories | | | | |
|  600001 Number Plate 220x170mm | | | Indoor / Outdoor | L220 x W170 x H10 |

• = This article is produced by order, with an expected delivery time of 3-4 weeks.