



Design: Svein Knudsen / Andrew Smith. Attractive, round wall luminaire with half-diffuser and four slits for indirect light that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. IP65 and vandal-resistant rating IK10.

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	633897 Tardo 2000 Graphite 870lm 3000K Ra>80 Sensor 14W LED 62 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct/Indirect, Opal	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x D105
	633896 Tardo 2000 Graphite 870lm 3000K Ra>80 Trailing edge 14W LED 62 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct/Indirect, Opal	Class I IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x D105
	621897 Tardo 2000 White 1070lm 3000K Ra>80 Sensor 14W LED 76 lm/W SDCM:3 L70/B50>100,000 Beam: 120°, Direct/Indirect, Opal	Class I IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x D105
	623896 Tardo Graphite 2xE27 On/Off Beam: 120°, Direct/Indirect, Opal	Class I IP65 IK10	On/Off	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H105 x D105
	611896 Tardo White 2xE27 On/Off Beam: 120°, Direct/Indirect, Opal	Class I IP65 IK10	On/Off	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H105 x D105