



Attractive, round wall luminaire with half-diffuser and slit that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Variants with integrated Twilight relay. IP65 and vandalresistant rating IK10.

Uno



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 644641 • Uno 1100 Black 440lm 3000K Ra>80 Sensor 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 644640 Uno 1100 Black 440lm 3000K Ra>80 Trailing edge 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 644644 Uno 1100 Black 440lm 3000K Ra>80 Twilight 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 643641 Uno 1100 Graphite 440lm 3000K Ra>80 Sensor 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 643640 Uno 1100 Graphite 440lm 3000K Ra>80 Trailing edge 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 643644 Uno 1100 Graphite 440lm 3000K Ra>80 Twilight 8W LED 55 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>641641 Uno 1100 White 530lm 3000K Ra>80 Sensor 8W LED 66 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 <p>641640 Uno 1100 White 530lm 3000K Ra>80 Trailing edge 8W LED 66 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 <p>641644 Uno 1100 White 530lm 3000K Ra>80 Twilight 8W LED 66 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
 <p>643642 Uno 1100 Graphite 460lm 4000K Ra>80 Trailing edge 8W LED 58 lm/W SDCM:3 L70/B10>50,000 Beam: 120°, Direct, Opal</p>	Class II IP65 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x D130
Accessories				
 <p>614580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Black</p>				L1000 x W290 x H220
 <p>623580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Graphite</p>				L1000 x W290 x H220
 <p>323 Tanto Diffuser</p>				Ø260 x H77
 <p>600580 Bollard Solo, Tanto, Uno, Primo and Arlon Round Anchoring set</p>				W330 x H524 x D260

• = This article is produced by order, with an expected delivery time of 3-4 weeks.