



View is a modern, slim mirror luminaire in two different lengths for mounting above a bathroom mirror. Mounting brackets for mounting over a bathroom cabinet, mirror cabinet or shelf are available as accessories. View is available with or without Schuko plug. Easy installation thanks to the quick coupling between the luminaire and wall bracket.

View

Sg

Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	111435 View Black w/ outlet 700lm 2700K Ra>90 Trailing edge 11W LED 64 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Indoor	L460 x W150 x H60 x D135
	114420 View Black 700lm 2700K Ra>90 Trailing edge 11W LED 64 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	114430 View 900 Black 1380lm 2700K Ra>90 Trailing edge 23W LED 60 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135
	197420 View Brushed steel 790lm 2700K Ra>90 Trailing edge 11W LED 72 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	111420 View White 890lm 2700K Ra>90 Trailing edge 11W LED 81 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	111430 View 900 White 1860lm 2700K Ra>90 Trailing edge 23W LED 81 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	111433 View White w/ outlet 890lm 2700K Ra>90 Trailing edge 11W LED 81 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W150 x H60 x D150
	111436 View Black w/ outlet 720lm 3000K Ra>90 Trailing edge 11W LED 65 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Indoor Screwless terminal block	L460 x W150 x H60 x D135
	114421 View Black 720lm 3000K Ra>90 Trailing edge 11W LED 65 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	114431 View 900 Black 1430lm 3000K Ra>90 Trailing edge 23W LED 62 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135
	197421 View Brushed steel 820lm 3000K Ra>90 Trailing edge 11W LED 75 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	111421 View White 920lm 3000K Ra>90 Trailing edge 11W LED 84 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	111431 View 900 White 1920lm 3000K Ra>90 Trailing edge 23W LED 83 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135
	111434 View White w/ outlet 920lm 3000K Ra>90 Trailing edge 11W LED 84 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W150 x H60 x D135
	114432 View Black 790lm 4000K Ra>90 Trailing edge 16W LED 49 lm/W SDCM:3 L70/B10>50,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	114433 View 900 Black 1480lm 4000K Ra>90 Trailing edge 23W LED 64 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135
	111422 View White 950lm 4000K Ra>90 Trailing edge 11W LED 86 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W135 x H60 x D135
	111432 View 900 White 1980lm 4000K Ra>90 Trailing edge 23W LED 86 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Direct, Opal	Class II IP44 (mounted horizontally) / IP20 (mounted vertically) IK10	Trailing edge	Surface, Indoor Screwless terminal block	L896 x W135 x H60 x D135

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	111437	Class I	Trailing edge	Surface, Indoor Screwless terminal block	L460 x W150 x H60 x D135
View White w/ outlet 950lm 4000K					
Ra>90 Trailing edge		IP44 (mounted horizontally) /			
11W LED		IP20 (mounted vertically)			
86 lm/W SDCM:3					
L90/B10>50,000, L80/B10>100,000		IK10			
Direct, Opal					
Accessories					
	100421				L172 x W66 x H33
View Black Furniture bracket					
	100420				L172 x W66 x H33
View White Furniture bracket					