

Zip Pro 3-Circuit



Three-phase rail spot with integrated powerful LED chip and driver. Driver can switch between three brightness levels using a jumper terminal. Mounted using global multi-adapter, which is ideal for SG's three-phase rail system (Shopline) as well as other systems where Global can be used. ZIP is made of powder-coated aluminium, flexible and able to be pointed in almost all directions, making it the obvious choice for shops and exhibitions.

Zip Pro 3-Circuit










Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	320736	Class I	On/Off	Surface, Indoor	Ø100 x L218 x W100 x
	Zip Pro 3-Circuit Black 40° 3370lm	IP20		ShopLine track (adapter included)	H148
	3000K Ra>90 On/Off				
	40W LED				
	84 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector				
	320734	Class I	On/Off	Surface, Indoor	Ø100 x L218 x W100 x
	Zip Pro 3-Circuit White 40° 3470lm	IP20		ShopLine track (adapter included)	H148
	3000K Ra>90 On/Off				
	40W LED				
	87 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector				
	320737	Class I	On/Off	Surface, Indoor	Ø100 x L218 x W100 x
	Zip Pro 3-Circuit Black 40° 3610lm	IP20		ShopLine track (adapter included)	H148
	4000K Ra>90 On/Off				
	40W LED				
	90 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector				
	3497	Class I	On/Off	Surface, Indoor	L218 x W100 x H219
	Zip Pro 3-Circuit Silver 40° 2840lm	IP20		ShopLine track (adapter included)	
	4000K Ra>90 On/Off				
	36W LED				
	79 lm/W SDCM:2 L80/B20>100,000, L90/B10>50,000 Beam: 40°, Direct, Reflector				
	320735	Class I	On/Off	Surface, Indoor	Ø100 x L218 x W100 x
	Zip Pro 3-Circuit White 40° 3710lm	IP20		ShopLine track (adapter included)	H148
	4000K Ra>90 On/Off				
	40W LED				
	93 lm/W SDCM:2 L90/B10>100,000 Beam: 40°, Direct, Reflector				
Accessories					
	314423	Class I		Surface, Indoor	Ø100 x H36
	Shipline Black Monopoint	IP20			
	312423	Class I		Surface, Indoor	Ø100 x H36
	Shipline White Monopoint	IP20			