

# Zip Zoom 1-Circuit



1 circuit rail spot for ZIP rail system with replaceable GU10 LED. Dimmable with phase dimmer.

Mounted using ZIP adapter, which is ideal for SG's one-phase ZIP rail system. Perfect colour rendering due to very high RA value. Made of powder-coated aluminium. Adjustable diffuser can change the light scattering, making ZIP Zoom perfect for use as effect lighting.

# Zip Zoom 1-Circuit









## Product- and environment images




# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>3529  <b>Zip Zoom Black DimToWarm 270lm</b>  <b>2000-2800K Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            45 lm/W SDCM:3            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128
 <p>3527  <b>Zip Zoom White DimToWarm</b>  <b>300lm 2000-2800K Ra&gt;90 Trailing</b>  <b>edge</b>  <b>6W LED</b>            50 lm/W SDCM:3            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128
 <p>3152  <b>Zip Zoom Black 270lm 2700K Ra&gt;90</b>  <b>Trailing edge</b>  <b>6W LED</b>            45 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128
 <p>3033  <b>Zip Zoom Brushed steel 270lm</b>  <b>2700K Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            45 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128
 <p>3032  <b>Zip Zoom White 310lm 2700K</b>  <b>Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            52 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128
 <p>3517  <b>Zip Zoom Brushed steel 280lm</b>  <b>3000K Ra&gt;90 Trailing edge</b>  <b>6W LED</b>            47 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 36°, Direct,</p>	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 3516 • <b>Zip Zoom White 320lm 3000K</b> <b>Ra&gt;90 Trailing edge</b> <b>6W LED</b> 53 lm/W SDCM:2 L70/B50>50,000 Beam: 36°, Direct,	<b>Class II</b> <b>IP20</b>	Trailing edge	Surface, Indoor Zip track (adapter included)	L78 x W73 x H128

• = This article is produced by order, with an expected delivery time of 3-4 weeks.