

Frame Round



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors and twilight are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Round



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605053 Frame Round Black 860lm 3000K Ra>80 Sensor 8W LED 108 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605051 Frame Round Black 670lm 3000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605052 Frame Round Black 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605063 Frame Round Graphite 860lm 3000K Ra>80 Sensor 8W LED 108 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605061 Frame Round Graphite 670lm 3000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605062 Frame Round Graphite 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 605043 Frame Round White 960lm 3000K Ra>80 Sensor 8W LED 120 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
 605041 Frame Round White 670lm 3000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
 605042 Frame Round White 670lm 3000K Ra>80 Twilight 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
 605203 Frame Round Black 670lm 4000K Ra>80 Sensor 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
 605081 Frame Round Black 670lm 4000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
 605064 Frame Round Graphite 890lm 4000K Ra>80 Sensor 8W LED 111 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605091 Frame Round Graphite 670lm 4000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605065 Frame Round White 670lm 4000K Ra>80 Sensor 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605071 Frame Round White 670lm 4000K Ra>80 Trailing edge 7W LED 96 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77

• = This article is produced by order, with an expected delivery time of 3-4 weeks.