

Frame Round Wall



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Round Wall



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605054 Frame Round Wall Black 390lm 3000K Ra>80 DALI-2 / Push Dim 7W LED 56 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	DALI-2 / Push Dim	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605056 Frame Round Wall Black 390lm 3000K Ra>80 Trailing edge 7W LED 56 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605066 Frame Round Wall Graphite 390lm 3000K Ra>80 Trailing edge 7W LED 56 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605046 Frame Round Wall White 390lm 3000K Ra>80 Trailing edge 7W LED 56 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77
	605092 Frame Round Wall Graphite 390lm 4000K Ra>80 Trailing edge 7W LED 56 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø270 x H77