

Frame Round Maxi



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors, twilight and emergency are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Round Maxi



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605198 Frame Round Maxi Black 1990lm 3000K Ra>80 DALI-2 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	DALI-2	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605155 Frame Round Maxi Black 1990lm 3000K Ra>80 Emergency 3H/trailing edge 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	Ø325 x H77
	8241000607 Frame Round Maxi Black 1990lm 3000K Ra>80 Emergency outdoor 3H 21W LED 95 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Plastic Opal	Class II IP66 IK10	Emergency outdoor 3H	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605153 Frame Round Maxi Black 2030lm 3000K Ra>80 Sensor 17W LED 119 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605151 Frame Round Maxi Black 1990lm 3000K Ra>80 Trailing edge 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605152 Frame Round Maxi Black 1990lm 3000K Ra>80 Twilight 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605165  Frame Round Maxi Graphite 1990lm 3000K Ra>80 Emergency 3H/trailing edge 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	Ø325 x H77
	605163 Frame Round Maxi Graphite 2030lm 3000K Ra>80 Sensor 17W LED 119 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605161 Frame Round Maxi Graphite 1990lm 3000K Ra>80 Trailing edge 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605162 Frame Round Maxi Graphite 1990lm 3000K Ra>80 Twilight 19W LED 105 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605145  Frame Round Maxi White 2320lm 3000K Ra>80 Emergency 3H/trailing edge 19W LED 122 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	Ø325 x H77
	605143 Frame Round Maxi White 2260lm 3000K Ra>80 Sensor 17W LED 133 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605144 • Frame Round Maxi White 2320lm 3000K Ra>80 Sensor Wireless 19W LED 122 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor Wireless	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605141 Frame Round Maxi White 2320lm 3000K Ra>80 Trailing edge 19W LED 122 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605142 • Frame Round Maxi White 2320lm 3000K Ra>80 Twilight 19W LED 122 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605181 Frame Round Maxi Black 2040lm 4000K Ra>80 Trailing edge 19W LED 107 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605182 Frame Round Maxi Graphite 2100lm 4000K Ra>80 Sensor 17W LED 124 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
	605191 Frame Round Maxi Graphite 2040lm 4000K Ra>80 Trailing edge 19W LED 107 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 605172 Frame Round Maxi White 2340lm 4000K Ra>80 Sensor 17W LED 138 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
 605171 Frame Round Maxi White 2380lm 4000K Ra>80 Trailing edge 19W LED 125 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	Ø325 x H77
Accessories				
 820307 Emergency battery 3 Hours 3.0Ah - Model No: B093				L137 x W27 x H27

• = This article is produced by order, with an expected delivery time of 3-4 weeks.