

Frame Square



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors and twilight are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Square



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605253 Frame Square Black 740lm 3000K Ra>80 Sensor 7.5W LED 99 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605251 Frame Square Black 630lm 3000K Ra>80 Trailing edge 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605252 Frame Square Black 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605263 Frame Square Graphite 740lm 3000K Ra>80 Sensor 7.5W LED 99 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605261 Frame Square Graphite 630lm 3000K Ra>80 Trailing edge 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605262 Frame Square Graphite 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605243 Frame Square White 860lm 3000K Ra>80 Sensor 7.5W LED 115 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605241 Frame Square White 630lm 3000K Ra>80 Trailing edge 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605242 Frame Square White 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605281  Frame Square Black 660lm 4000K Ra>80 Trailing edge 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605292  Frame Square Graphite 660lm 4000K Ra>80 Sensor 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
	605291 Frame Square Graphite 660lm 4000K Ra>80 Trailing edge 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605271	Class II	Trailing edge	Surface, Indoor / Outdoor	L240 x W240 x H77
	Frame Square White 660lm 4000K	IP66		Screwless terminal block	
	Ra>80 Trailing edge	IK10			
	7W LED				
	94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal				

• = This article is produced by order, with an expected delivery time of 3-4 weeks.