

Frame Square Maxi



Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors, twilight and emergency are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.

Frame Square Maxi



Product- and environment images



Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605355  Frame Square Maxi Black 1980lm 3000K Ra>80 Emergency 3H/trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L310 x W310 x H77
	8241000608  Frame Square Maxi Black 1980lm 3000K Ra>80 Emergency outdoor 3H 22W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Plastic Opal	Class II IP66 IK10	Emergency outdoor 3H	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605353 Frame Square Maxi Black 2090lm 3000K Ra>80 Sensor 19W LED 110 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605351 Frame Square Maxi Black 1980lm 3000K Ra>80 Trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605352 Frame Square Maxi Black 1980lm 3000K Ra>80 Twilight 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605365  Frame Square Maxi Graphite 1980lm 3000K Ra>80 Emergency 3H/trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency 3H/trailing edge	Surface, Indoor Screwless terminal block	L310 x W310 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605363 Frame Square Maxi Graphite 2090lm 3000K Ra>80 Sensor 19W LED 110 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor	L310 x W310 x H77
	605366 Frame Square Maxi Graphite 1980lm 3000K Ra>80 Sensor Emergency 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor Emergency	Surface, Indoor	L310 x W310 x H77
	605361 Frame Square Maxi Graphite 1980lm 3000K Ra>80 Trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor	L310 x W310 x H77
	605362 Frame Square Maxi Graphite 1980lm 3000K Ra>80 Twilight 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor	L310 x W310 x H77
	605345 Frame Square Maxi White 1980lm 3000K Ra>80 Emergency 3H/trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Emergency	Surface, Indoor	L310 x W310 x H77
	605343 Frame Square Maxi White 2420lm 3000K Ra>80 Sensor 19W LED 127 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor	L310 x W310 x H77

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	605344 ● Frame Square Maxi White 1980lm 3000K Ra>80 Sensor Wireless 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor Wireless	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605341 Frame Square Maxi White 1980lm 3000K Ra>80 Trailing edge 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605342 Frame Square Maxi White 1980lm 3000K Ra>80 Twilight 21W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605394 Frame Square Maxi Black 2370lm 4000K Ra>80 Sensor 21W LED 113 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605381 Frame Square Maxi Black 2370lm 4000K Ra>80 Trailing edge 21W LED 113 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
	605392 Frame Square Maxi Graphite 2370lm 4000K Ra>80 Sensor 21W LED 113 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Sensor	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 605391 Frame Square Maxi Graphite 2370lm 4000K Ra>80 Trailing edge 21W LED 113 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
 605371 Frame Square Maxi White 2370lm 4000K Ra>80 Trailing edge 21W LED 113 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal	Class II IP66 IK10	Trailing edge	Surface, Indoor / Outdoor Screwless terminal block	L310 x W310 x H77
Accessories				
 820307 Emergency battery 3 Hours 3.0Ah - Model No: B093				L137 x W27 x H27

• = This article is produced by order, with an expected delivery time of 3-4 weeks.