

Bell



Ceiling lamp with deep-mounted light source that provides a comfortable light without glare. Supplied with a ceiling rose. Can also be fitted in adapters for Zip 230V rails and ShopLine 3-phase rails. Bell comes in three sizes and three different color combinations: Black/White, White/White and Black/Gold.

Bell



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 312362 Bell Black/Gold Mini 240lm 2700K Ra>90 Trailing edge 5W LED 48 lm/W SDCM:3 L70/B50>50,000 Beam: 137°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø160 x H205
 312365 Bell Black/Gold Midi 560lm 2700K Ra>90 Trailing edge 10W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 127°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø230 x H261
 312368 Bell Black/Gold Maxi 820lm 2700K Ra>90 Trailing edge 15W LED 55 lm/W SDCM:3 L70/B50>50,000 Beam: 130°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
 312361 Bell Black/White Mini 250lm 2700K Ra>90 Trailing edge 5W LED 50 lm/W SDCM:3 L70/B50>50,000 Beam: 100°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø160 x H205
 312364 Bell Black/White Midi 590lm 2700K Ra>90 Trailing edge 10W LED 59 lm/W SDCM:3 L70/B50>50,000 Beam: 106°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø230 x H261
 312367 Bell Black/White Maxi 840lm 2700K Ra>90 Trailing edge 15W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 104°, Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 312369 Bell White/Gold Mini 240lm 2700K Ra>90 Trailing edge 5W LED 48 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø160 x H205
 312370 Bell White/Gold Midi 560lm 2700K Ra>90 Trailing edge 10W LED 56 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø230 x H261
 312371 Bell White/Gold Maxi 820lm 2700K Ra>90 Trailing edge 15W LED 55 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal	Class II IP20	Trailing edge	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
Accessories				
 830917 E27 LED White DimToWarm 1200lm 2000-2800K Ra>80				Ø95 x L135
 830922 E27 LED White DimToWarm 350lm 2000-2800K Ra>80				Ø45 x L79
 830913 E27 LED DimToWarm 806lm 2000-2800K Ra>80				Ø60 x L110
 830916 E27 LED White 1200lm 2700K Ra>90				Ø95 x L136
 830911 E27 806lm 2700K Ra>90				Ø60 x L110
 830918 E27 LED White 1200lm 3000K Ra>90				Ø95 x L136

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
	3107			L84 x W23 x H90
	Zip 230V Black Adapter - Pendant			
	3109			L93 x W32 x H62
	Shopline Black Pendant Adapter			
	3163			Ø114 x L114 x W114 x H135
	Black Ceiling Box for Pendant			
	314331			Ø102 x L102 x W102 x H25
	Black Round Ceiling Box for Pendant			
	314334			Ø94 x H51
	Black Recessed Ceiling Box for Pendant			
	3046			L84 x W23 x H90
	Zip 230V White Adapter - Pendant			
	3108			L93 x W32 x H62
	Shopline White Pendant Adapter			
	3164			Ø114 x L114 x W114 x H135
	White Ceiling Box for Pendant			
	314332			Ø102 x L102 x W102 x H25
	White Round Ceiling Box for Pendant			
	314333			Ø94 x H51
	White Recessed Ceiling Box for Pendant			