



Hovden is a premium range of garden spots for creating outdoor lighting environments. It is made of sturdy machined aluminum, powder coated. Comes with a bracket that can be fixed to wall or ground, or to a ground spear. The head can be rotated 360 degrees, allowing for flexible installation. Plug and play, delivered with 2 meter outdoor cable and plug. Waterproof IP67. Phase-cut dimmable. The reflector provides 15 and 36-degree beam angle for spot or flood effects. Additional anti-glare visors are available.

## Product- and environment images



# Article codes



| Article  | Protection                                   | Control gear  | Mounting/Connection                                     | Dimensions       |
|--|--|---------------|---|------------------|
|  <p>630078<br/> <b>Hovden Corten Mini 550lm 2700K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>                     69 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p>  | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100 |
|  <p>630081<br/> <b>Hovden Corten Micro 230lm 2700K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>4W LED</b><br/>                     58 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p> | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L82 x W36 x H85  |
|  <p>630062<br/> <b>Hovden Graphite Micro 230lm 2700K Ra&gt;80 Trailing edge</b><br/> <b>4W LED</b><br/>                     58 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p>           | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L82 x W36 x H85  |
|  <p>630063<br/> <b>Hovden Graphite Mini 570lm 2700K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>                     71 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p>          | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L90 x W46 x H100 |
|  <p>630083<br/> <b>Hovden Black Micro 250lm 3000K Ra&gt;80 Trailing edge</b><br/> <b>4W LED</b><br/>                     63 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p>            | <b>Class I</b><br><b>IP67</b><br><b>IK10</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L82 x W36 x H85  |
|  <p>630084<br/> <b>Hovden Black Mini 550lm 3000K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>                     69 lm/W SDCM:3<br/>                     L70/B10&gt;100,000<br/>                     Beam: 36°, Direct, Lens</p>             | <b>Class I</b><br><b>IP67</b><br><b>IK10</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100 |

# Article codes



| Article   | Protection                                   | Control gear  | Mounting/Connection                                     | Dimensions        |
|---|--|---------------|---|-------------------|
|  <p>630085<br/> <b>Hovden Black Midi 1140lm 3000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           95 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>    | <b>Class I</b><br><b>IP67</b><br><b>IK10</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630086<br/> <b>Hovden Black Maxi 2010lm 3000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>23W LED</b><br/>           87 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>    | <b>Class I</b><br><b>IP67</b><br><b>IK10</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L150 x W89 x H147 |
|  <p>630079<br/> <b>Hovden Corten Mini 550lm 3000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>           69 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>     | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100  |
|  <p>630080<br/> <b>Hovden Corten Midi 1140lm 3000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           95 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p> | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630082<br/> <b>Hovden Corten Micro 250lm 3000K</b><br/> <b>Ra&gt;80 Trailing edge</b><br/> <b>4W LED</b><br/>           63 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>  | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L82 x W36 x H85   |
|  <p>630000<br/> <b>Hovden Graphite Mini 540lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>           68 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p> | <b>Class I</b><br><b>IP67</b>                | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100  |

# Article codes



| Article   | Protection                    | Control gear  | Mounting/Connection                                     | Dimensions        |
|---|-------------------------------|---------------|---|-------------------|
|  <p>630001<br/> <b>Hovden Graphite Mini 550lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>           69 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>     | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100  |
|  <p>630004<br/> <b>Hovden Graphite Midi 1060lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           88 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p>   | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630005<br/> <b>Hovden Graphite Midi 1140lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           95 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>   | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630008<br/> <b>Hovden Graphite Maxi 2010lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>23W LED</b><br/>           87 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p> | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L150 x W89 x H147 |
|  <p>630009<br/> <b>Hovden Graphite Maxi 2010lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>23W LED</b><br/>           87 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p> | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L150 x W89 x H147 |
|  <p>630048<br/> <b>Hovden Graphite Micro 250lm</b><br/> <b>3000K Ra&gt;80 Trailing edge</b><br/> <b>4W LED</b><br/>           63 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>  | <b>Class I</b><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L82 x W36 x H85   |

# Article codes



| Article   | Protection                        | Control gear  | Mounting/Connection                                     | Dimensions        |
|---|-----------------------------------|---------------|---|-------------------|
|  <p>630002<br/> <b>Hovden Graphite Mini 600lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>           75 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p>     | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100  |
|  <p>630003<br/> <b>Hovden Graphite Mini 620lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>8W LED</b><br/>           78 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p>     | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L95 x W46 x H100  |
|  <p>630006<br/> <b>Hovden Graphite Midi 1080lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           90 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p>   | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630007<br/> <b>Hovden Graphite Midi 1160lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>12W LED</b><br/>           97 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p> | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L100 x W61 x H116 |
|  <p>630010<br/> <b>Hovden Graphite Maxi 2070lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>23W LED</b><br/>           90 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 15°, Direct, Lens</p> | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L150 x W89 x H147 |
|  <p>630011<br/> <b>Hovden Graphite Maxi 2080lm</b><br/> <b>4000K Ra&gt;80 Trailing edge</b><br/> <b>23W LED</b><br/>           90 lm/W SDCM:3<br/>           L70/B10&gt;100,000<br/>           Beam: 36°, Direct, Lens</p> | <b>Class I</b><br><br><b>IP67</b> | Trailing edge | Surface, Outdoor<br>Cable 2m<br>Includes cable and plug | L150 x W89 x H147 |

## Accessories

# Article codes



| Article   | Protection | Control gear | Mounting/Connection | Dimensions       |
|---|------------|--------------|---------------------|------------------|
|  78740<br><b>Gelbox-I Black Connector</b>      |            |              |                     | L135 x W48 x H30 |
|  78741<br><b>Gelbox-Y Black Connector</b>      |            |              |                     | L148 x W86 x H30 |
|  630093<br><b>Hovden Black Mini Visor</b>      |            |              |                     | L50 x W50 x H50  |
|  630094<br><b>Hovden Black Midi Visor</b>      |            |              |                     | L65 x W65 x H65  |
|  630095<br><b>Hovden Black Maxi Visor</b>      |            |              |                     | L93 x W83 x H93  |
|  630096<br><b>Hovden Black Micro Visor</b>     |            |              |                     | L42 x W38 x H42  |
|  630097<br><b>Hovden Corten Mini Visor</b>   |            |              |                     | L50 x W50 x H50  |
|  630098<br><b>Hovden Corten Midi Visor</b>   |            |              |                     | L65 x W65 x H65  |
|  630100<br><b>Hovden Corten Micro Visor</b>  |            |              |                     | L42 x W38 x H42  |
|  630026<br><b>Hovden Graphite Earthspear</b> |            |              |                     | L44 x W44 x H207 |
|  630027<br><b>Hovden Graphite Mini Visor</b> |            |              |                     | L50 x W50 x H50  |
|  630028<br><b>Hovden Graphite Midi Visor</b> |            |              |                     | L65 x W65 x H65  |
|  630029<br><b>Hovden Graphite Maxi Visor</b> |            |              |                     | L93 x W83 x H93  |

# Article codes



| Article  | Protection | Control gear | Mounting/Connection | Dimensions      |
|--|------------|--------------|---------------------|-----------------|
|  630058<br><b>Hovden Graphite Micro Visor</b> |            |              |                     | L42 x W38 x H42 |