



Flom provides energy- and money-saving outdoor lighting which can be used for the workplace, facade or the garden. Flom also comes with a daylight and motion sensor (PIR). After dark (below 3 lux), Flom automatically switches on when it detects movement at a distance of 2 to 6 metres (adjustable). It switches on within 5 seconds and stays on for 5 minutes (adjustable). It switches off automatically when no further movement is detected. Adjustable angle of bracket.

Flom



Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 630018 Flom Graphite Mini 1060lm 3000K Ra>80 On/Off 10W LED 106 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L120 x W95 x H44
 630020 Flom Graphite Midi 2610lm 3000K Ra>80 On/Off 23W LED 113 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L160 x W130 x H52
 630024 Flom Graphite Maxi 4640lm 3000K Ra>80 On/Off 42W LED 110 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L200 x W160 x H64
 630019 Flom Graphite Mini 1060lm 3000K Ra>80 PIR Sensor 10W LED 106 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L120 x W95 x H44
 630021 Flom Graphite Midi 2610lm 3000K Ra>80 PIR Sensor 23W LED 113 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L160 x W130 x H52
 630025 Flom Graphite Maxi 4640lm 3000K Ra>80 PIR Sensor 42W LED 110 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L200 x W160 x H64

Article codes



Article		Protection	Control gear	Mounting/Connection	Dimensions
	630050	Class I	On/Off	Surface, Outdoor	L200 x W160 x H64
	Flom White Maxi 5400lm 3000K	IP65		Cable 1.5m	
	Ra>80 On/Off	IK06			
	42W LED				
	129 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				
	630052	Class I	On/Off	Surface, Outdoor	L160 x W130 x H52
	Flom White Midi 2910lm 3000K	IP65		Cable 1.5m	
	Ra>80 On/Off	IK06			
	23W LED				
	127 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				
	630054	Class I	On/Off	Surface, Outdoor	L120 x W95 x H44
	Flom White Mini 1290lm 3000K	IP65		Cable 1.5m	
	Ra>80 On/Off	IK06			
	10W LED				
	129 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				
	630051	Class I	PIR Sensor	Surface, Outdoor	L200 x W160 x H64
	Flom White Maxi 5400lm 3000K	IP65		Cable 1.5m	
	Ra>80 PIR Sensor	IK06			
	42W LED				
	129 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				
	630053	Class I	PIR Sensor	Surface, Outdoor	L160 x W130 x H52
	Flom White Midi 2910lm 3000K	IP65		Cable 1.5m	
	Ra>80 PIR Sensor	IK06			
	23W LED				
	127 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				
	630055	Class I	PIR Sensor	Surface, Outdoor	L120 x W95 x H44
	Flom White Mini 1290lm 3000K	IP65		Cable 1.5m	
	Ra>80 PIR Sensor	IK06			
	10W LED				
	129 lm/W SDCM:3				
	L80/B50>50,000				
	Beam: 100°, Direct, Glass Frosted				

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 630034 Flom Graphite Mini 1140lm 4000K Ra>80 On/Off 10W LED 114 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L120 x W95 x H44
 630036 Flom Graphite Midi 2710lm 4000K Ra>80 On/Off 23W LED 118 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L160 x W130 x H52
 630040 Flom Graphite Maxi 4980lm 4000K Ra>80 On/Off 42W LED 119 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	On/Off	Surface, Outdoor Cable 1.5m	L200 x W160 x H64
 630035 Flom Graphite Mini 1140lm 4000K Ra>80 PIR Sensor 10W LED 114 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L120 x W95 x H44
 630037 Flom Graphite Midi 2710lm 4000K Ra>80 PIR Sensor 23W LED 118 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L160 x W130 x H52
 630041 Flom Graphite Maxi 4980lm 4000K Ra>80 PIR Sensor 42W LED 119 lm/W SDCM:3 L80/B50>50,000 Beam: 100°, Direct, Glass Frosted	Class I IP65 IK06	PIR Sensor	Surface, Outdoor Cable 1.5m	L200 x W160 x H64

Accessories

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 630090 Flom Graphite Sign Arm				L695 x W125 x H87
 630091 Flom White Sign Arm				L695 x W125 x H87