

Disc 285x285 TW



Energy efficient surface-mounted LED luminaire with a slim profile ensuring a modern look. Square and round available in multiple sizes and lumens. Opalprismatic diffuser provides a glare-free light. The luminaire is produced in a matt black or white powder-coated aluminium finish. Simple installation with quick connections between fixture and back plate that can be screwed straight onto all known ceiling boxes. Visible cabling also possible. Tunable White 2700-6500K LEDDim.

Disc 285x285 TW



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>606079 Disc 285X285 TW Black 1740lm (@6500K) 2700-6500K Ra>80 TW LEDDim 19W LED 92 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism</p>	Class II IP20 IK10	TW LEDDim	Surface, Indoor Screwless terminal block	L283 x W283 x H55
 <p>606062 Disc 285X285 TW White 1890lm (@6500K) 2700-6500K Ra>80 TW LEDDim 19W LED 99 lm/W SDCM:3 L80/B20>100,000, L90>50,000 Beam: 85°, Direct, Opalprism</p>	Class II IP20 IK10	TW LEDDim	Surface, Indoor Screwless terminal block	L283 x W283 x H55
Accessories				
 <p>606095 Disc/Frosta Black Pendant Adapter</p>				L5000 x W102 x H22
 <p>606094 Disc/Frosta White Pendant Adapter</p>				L5000 x W102 x H22