

# Inspire R



Inspire R is a rectangular recessed downlight for indoor use. With cubist black reflectors it has very low glare and harmonious non-flickering light with a well-defined light pattern. Inspire R is suitable for use in high-end residential and commercial environments.

# Inspire R



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212422  <b>Inspire R Black 150 450lm 2700K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      56 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212428  <b>Inspire R Black 300 900lm 2700K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      60 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor Screwless terminal block	L303 x W62 x H40
 <p>212421  <b>Inspire R Black 150 450lm 2700K Ra</b>  <b>98 Trailing edge</b>  <b>8W LED</b>                      56 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212427  <b>Inspire R Black 300 900lm 2700K Ra</b>  <b>98 Trailing edge</b>  <b>15W LED</b>                      60 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40
 <p>212416  <b>Inspire R White 150 450lm 2700K</b>  <b>Ra 98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      56 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L163 x W62 x H40
 <p>212434  <b>Inspire R White 300 900lm 2700K</b>  <b>Ra 98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      60 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor Screwless terminal block	L303 x W62 x H40

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212415  <b>Inspire R White 150 450lm 2700K</b>  <b>Ra 98 Trailing edge</b>  <b>8W LED</b>                      56 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212433  <b>Inspire R White 300 900lm 2700K</b>  <b>Ra 98 Trailing edge</b>  <b>15W LED</b>                      60 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40
 <p>212424  <b>Inspire R Black 150 470lm 3000K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      59 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L163 x W62 x H40
 <p>212430  <b>Inspire R Black 300 950lm 3000K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      63 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L303 x W62 x H40
 <p>212423  <b>Inspire R Black 150 470lm 3000K Ra</b>  <b>98 Trailing edge</b>  <b>8W LED</b>                      59 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212429  <b>Inspire R Black 300 950lm 3000K Ra</b>  <b>98 Trailing edge</b>  <b>15W LED</b>                      63 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212418  <b>Inspire R White 150 470lm 3000K</b>  <b>Ra 98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      59 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L163 x W62 x H40
 <p>212436  <b>Inspire R White 300 950lm 3000K</b>  <b>Ra 98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      63 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L303 x W62 x H40
 <p>212417  <b>Inspire R White 150 470lm 3000K</b>  <b>Ra 98 Trailing edge</b>  <b>8W LED</b>                      59 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212435  <b>Inspire R White 300 950lm 3000K</b>  <b>Ra 98 Trailing edge</b>  <b>15W LED</b>                      63 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40
 <p>212426  <b>Inspire R Black 150 490lm 4000K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      61 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L163 x W62 x H40
 <p>212432  <b>Inspire R Black 300 980lm 4000K Ra</b>  <b>98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      65 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor Screwless terminal block	L303 x W62 x H40

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212425  <b>Inspire R Black 150 490lm 4000K Ra 98 Trailing edge</b>  <b>8W LED</b>                      61 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212431  <b>Inspire R Black 300 980lm 4000K Ra 98 Trailing edge</b>  <b>15W LED</b>                      65 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40
 <p>212420  <b>Inspire R White 150 490lm 4000K Ra 98 DALI-2 / Push Dim</b>  <b>8W LED</b>                      61 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L163 x W62 x H40
 <p>212438  <b>Inspire R White 300 980lm 4000K Ra 98 DALI-2 / Push Dim</b>  <b>15W LED</b>                      65 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	DALI-2 / Push Dim	Recessed, Indoor 5 pol Linect / screwless terminal block	L303 x W62 x H40
 <p>212419  <b>Inspire R White 150 490lm 4000K Ra 98 Trailing edge</b>  <b>8W LED</b>                      61 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L163 x W62 x H40
 <p>212437  <b>Inspire R White 300 980lm 4000K Ra 98 Trailing edge</b>  <b>15W LED</b>                      65 lm/W SDCM:2                      L90/B10&gt;100,000                      Beam: 55°, Direct, Lens</p>	<b>Class II SELV</b> <b>IP20</b>	Trailing edge	Recessed, Indoor Screwless terminal block	L303 x W62 x H40

## Accessories

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 212482 <b>Inspire Gold 150 Reflector</b>				L140 x W38 x H16
 212483 <b>Inspire Gold 300 Reflector</b>				L280 x W38 x H16
 212480 <b>Inspire White 150 Reflector</b>				L140 x W38 x H16
 212481 <b>Inspire White 300 Reflector</b>				L280 x W38 x H16
 820090 <b>Emergencybox Adapter kit for downlight</b>				L250 x W13 x H13
 8246094364 <b>Emergencybox On-Off/Trailing edge / EM Self test, Emergency 3 hours</b>				L270 x W75 x H35
 8246094500 <b>Emergencybox Driver DALI / EM DALI/Self test, Emergency 3 hours</b>				L270 x W75 x H35