



Namsen is a cost-effective luminaire with dimmable integrated LED. The versions with on-off switch and 2 sockets (16A) are suitable for under-cupboard lighting in the kitchen, laundry room, etc. Separate connection for socket and light. The version without a switch or plug is great for general lighting in hallways, storage rooms, lofts etc. Easy installation and cable feed on three sides. The front can be rotated to place the connectors on the right or left side.

Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 112022 Namsen 600 White w/ 2 x outlet 880lm 2700K Ra>80 Trailing edge 10W LED 88 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L595 x W69 x H46
 112024 Namsen 1200 White w/ 2 x outlet 2220lm 2700K Ra>80 Trailing edge 23W LED 97 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L1195 x W69 x H46
 112027 Namsen 900 White w/ 2 x outlet 1410lm 2700K Ra>80 Trailing edge 15W LED 94 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L920 x W69 x H46
 112031 Namsen 600 White w/ 2 x outlet 920lm 3000K Ra>80 DALI-2 / Push Dim Dim 12W LED 77 lm/W SDCM:3 L80/B50>50,000 Direct, Opal	Class I IP20 IK08	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L635 x W69 x H46
 112032 Namsen 1200 White w/ 2 x outlet 2110lm 3000K Ra>80 DALI-2 / Push Dim Dim 27W LED 78 lm/W SDCM:3 L80/B50>50,000 Direct, Opal	Class I IP20 IK08	DALI-2 / Push Dim	Surface, Indoor Screwless terminal block	L1195 x W69 x H46
 112023 Namsen 600 White w/ 2 x outlet 900lm 3000K Ra>80 Trailing edge 10W LED 90 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L595 x W69 x H46

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 112025 Namsen 1200 White w/ 2 x outlet 2280lm 3000K Ra>80 Trailing edge 23W LED 99 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L1195 x W69 x H46
 112026 Namsen 1200 White 2280lm 3000K Ra>80 Trailing edge 23W LED 99 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L1195 x W69 x H46
 112029 Namsen 900 White w/ 2 x outlet 1460lm 3000K Ra>80 Trailing edge 15W LED 97 lm/W SDCM:3 L80/B10>100,000 Direct, Opal	Class I IP20 IK08	Trailing edge	Surface, Indoor Screwless terminal block	L920 x W69 x H46