

Farm 66



Farm 66 is a very hardy luminaire, especially suitable for pig farms and the like. The LED compartment has an extra high protection rating to withstand ammonia gasses in such environments. The luminaire housing is made of hard UV-stabilised and anti-chemical coated polycarbonate. The coating is resistant to ammonia, washing detergents* etc, and makes it suitable also for car wash halls and similar. It is easy to install by just snapping into mounting clips and using the unique one-hand closing mechanism at both ends. The looping options with double cable gland in each end and through wiring gives full flexibility for larger installations. * Farm 66 is resistant to aqueous salt solutions up to about 60°C and diluted acids. It has limited resistance to alcohols, aliphatic hydrocarbons, and diluted alkalis, and is not resistant to concentrated mineral acids and alkalis, ammonia, amines, aromatic and/or halogenated hydrocarbons, esters, ethers, ketones, or solvents such as methyl ethylketone, tetrahydrofuran, toluene, and dimethyl-formamide.

Farm 66



Product- and environment images



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|---|--|-------------------|--|--------------------|
|  <p>120012 Farm 66 1500 Grey 5860lm 4000K Ra>80 DALI-2 / Push Dim 43W LED 136 lm/W SDCM:3 L90/B50>50,000 Direct, Opal</p> | Class I IP66 IK08 | DALI-2 / Push Dim | Surface, Indoor 7-pole screwless terminal block with 5x2,5mm ² (+DALI) through wiring | L1460 x W112 x H67 |
|  <p>120014 Farm 66 Pro 1500 Grey 9820lm 4000K Ra>80 DALI-2 / Push Dim 65W LED 151 lm/W SDCM:3 L80/B10>100,000 Direct, Opal</p> | Class I IP66 IK08 | DALI-2 / Push Dim | Surface, Indoor 7-pole screwless terminal block with 5x2,5mm ² (+DALI) through wiring | L1460 x W112 x H67 |
|  <p>120009 Farm 66 1200 Grey 4030lm 4000K Ra>80 On/Off 34W LED 119 lm/W SDCM:3 L90/B50>50,000 Direct, Opal</p> | Class I IP66 IK08 | On/Off | Surface, Indoor 5-pole screwless terminal block with 5x2,5mm ² through wiring | L1174 x W112 x H67 |
|  <p>120010 Farm 66 1500 Grey 5720lm 4000K Ra>80 On/Off 47W LED 122 lm/W SDCM:3 L90/B50>50,000 Direct, Opal</p> | Class I IP66 IK08 | On/Off | Surface, Indoor 5-pole screwless terminal block with 5x2,5mm ² through wiring | L1460 x W112 x H67 |
| Accessories | | | | |
|  <p>120006 45° Fastening</p> | | | | L42 x W42 x H15 |
|  <p>820259 Start current limiter DIN 16A</p> | | | | L90 x W18 x H58 |
|  <p>8249044900 Wirekit 2x5m</p> | | | | L19 x W25 x H150 |